

General information

Depending on the intensity of use, a floor's sealing coat is subject to a natural wearout. Therefore, regular care according to DIN 18356 is an absolute necessity. If the surface has become defective due to heavy wear, it must be sanded and resealed. Sealing is an artisan process. This means that small disruptions may occur on the surface (e.g. dust particles). However, this does not have any influence on the floor's durability.

Wood is a natural product. It expands and contracts and permanently adapts to the humidity and room climate. During the heating period, the relative air humidity decreases significantly. The wood reacts to this and releases humidity itself - it contracts. This is visible by joint/gap building in the parquet floor. The longer and the more intensely rooms are heated, the dryer the air and the wider the joints in the floor. The broadest joints are therefore to be expected towards the end of the heating period. At the end of summer they are generally most narrow or closed again. In order to counteract joint/gap building to a certain extent, you may attach water evaporators to the radiators or have an appropriate number of foliage plants in the house.

- Newly sealed floors must be allowed to dry up to 24 hours before they can be used. Please arrange furniture carefully. Do not just push it!
- Give your newly sealed floor at least 10 days time before you expose it to its normal wear, or before using care products.
- Do not use steel splints or sharp cleaning pads. Dirt and sand have a sandpaper effect and are to be removed immediately.
- For cleaning and care do only use high-quality products that are compatible with each other.
- By providing dirt collection zones in front of the entrance, you can reduce the dirt insertion inside significantly.
- In order to prevent scratches, you may attach small pieces of felt under your furniture. If you have furniture with rollers, protect the floor with floor mats.
- If you use skid-reducing under-carpet mats, take care that they do not contain any softeners.

Care and cleaning intervals

Wear intensity	Basic care and reconditioning OLI-AQUA POLISH basic parquet care 15.95	Maintenance OLI-AQUA CARE parquet wiping care 15.94	Basic cleaning OLI-AQUA CLEAN basic parquet cleaner 15.97
Normal/medium (Living rooms and bedrooms)	10 days after sealing, every 3 months for reconditioning and after each basic cleaning	weekly	every 12 months
High (corridors, offices)	10 days after sealing, monthly for reconditioning and after each basic cleaning	every 2 days	every 6 months
Intensive (multi-purpose halls, shops, restaurants, schools)	10 days after sealing, monthly for reconditioning and after each basic cleaning	daily	every 3 months
gymnasiums and sports halls	10 days after sealing and after each basic cleaning, with OLI-AQUA POLISHsport sports floor care 15.96	depending on the wear intensity, with OLI-AQUA POLISHsport sports floor care 15.96	as necessary



Care instructions

for wooden floors sealed according to DIN 18356

Your floor was sealed on the

with

Distributor/Signature

┌

└

Your wooden or parquet floor is protected with a high-quality sealing coat from dirt and wetness. In order that this protection is a durable one and you can enjoy the beauty of your floor over many years, you should heed the following advice. We promise that your wooden or parquet floor will repay you for it by gaining an ever more beautiful and individual natural patina.

First of all, the floor must be cleaned dry (e.g. with a broom or vacuum cleaner with a brush). Do a wet cleaning afterwards. Take care not to leave any puddles due to the danger of wood swelling. Do only mop the floor slightly damp, i.e. with a well wrung-out cloth or mop.

Primary care and reconditioning



Primary care should be conducted 10 days after the sealing the earliest as well as after each basic cleaning. **OLI-AQUA POLISH basic parquet care 15.95** protects the parquet from walking marks and scratches. While OLI-AQUA POLISH basic parquet care glossy gives the parquet a satin-finished look, OLI-AQUA POLISH basic parquet care matt gives it a silk matt-finished one.

Apply OLI-AQUA POLISH basic parquet care undiluted, thinly and evenly with a lint-free broad wetmop or cotton cloth. Allow the floor to dry for at least 12 hours before exposing it to its use. If you wish a higher gloss level, repeat the application in cross direction as soon as the coat is touch-dry. Do not polish! Coverage: approx. 20-25g/sqm per coat.

Maintenance



For maintenance care we recommend you to use **OLI-AQUA CARE parquet wiping care 15.94**. This product removes dirt and grease reliably. Add approx. 50 ml OLI-AQUA CARE parquet wiping care to 10 litres of clear water and wipe the floor slightly damp with a wrung-out mop, sponge or cloth. For the removal of grease spots, heel abrasion marks and other stubborn sorts of dirt,

apply OLI-AQUA CARE parquet wiping care undiluted with a scratch-free white pad and then take up the dirt and cleaner residues with a wrung-out cloth.

Basic cleaning



For extremely pertinacious sorts of dirt and cleaner residues that cannot be removed by common wiping care anymore, we recommend our soft intensive cleaner **OLI-AQUA CLEAN basic parquet cleaner 15.97**.

Apply OLI-AQUA CLEAN basic parquet cleaner undiluted with a lint-free broad wetmop. Take up etched dirt and cleaner residues with a water Hoover or a dry mop after a residence time of approx. 10 minutes. Wipe the floor slightly damp with clear water afterwards. A basic cleaning should be carried out as seldom as possible.

Sports floor care



For the maintenance and care of gymnasium floors we recommend you to use **OLI-AQUA POLISHsport sports floor care 15.96**. This product is certified in compliance with DIN 18032-2; it is skid-resistant, increases the floor's wear-resistance and removes abrasion marks reliably.

OLI-AQUA POLISHsport sports floor care is a multi-purpose product and can thus be used for basic care as well as for wiping care (diluted).

■ **Basic care:** Apply the product undiluted, thinly and evenly with a lint-free broad wetmop on the thoroughly cleaned floor. Repeat the application after a drying time of approx. 20-30 minutes. Coverage: 15-30 ml/sqm.

■ **Wiping care:** Dilute OLI-AQUA POLISHsport sports floor care (1 litre per 10 litres of water) and mop the floor slightly damp with this dilution.

Oli Lacke GmbH

Phone +49 (0) 3 72 08/ 84-0

Fax +49 (0) 3 72 08/ 84-382

info@oli-lacke.de

www.oli-lacke.de