



OLI-FINISH Holzlasuren - Wood glazes -

Product description

OLI-FINISH alkyd resin-based transparent wood glazes do not only enhance the beauty of the wood, but also protect it durably against weathering (moisture and UV radiation). The natural beauty of the wood is retained and can be refreshed with only little effort. Since the products do not contain any fungicides, OLI-FINISH wood glazes are both suitable for indoor and outdoor application.

Properties

- in compliance with the EU Decopaint Directive
- free of pentachlorophenol (PCP) und lindane (HCH)
- open-pore with deep penetration
- good protection against weathering
- decorative effect through the accentuation of the wood grain
- all colours intermixable
- also available in colourless (only for indoors and for the optical brightening of the colours)

Ordering information

OLI-FINISH Holzlasuren - Wood glazes -				
	Ordering code			Ordering code
Colourless	700 900 18		Walnut	700 905 01
Pine	700 903 09		Palisander	700 908 00
Oak	700 904 05		Ebony	700 901 06
Cherry	700 902 02		Fir green	700 907 04
Container sizes	5 ltrs		Container sizes	5 ltrs
Thinner V 110	912 601 00		Thinner V 110	912 601 00

Labelling

For labelling details and safety instructions, please refer to our safety datasheet at www.oli-lacke.de.

Technical data

Shelf-life in factory sealed containers:	12 months
Thinner:	V 110
Curing agent:	-
Mixing ratio:	-
Air drying at +23°C/65% rh	
Dust dry:	3 h
Overcoatable:	over night
Sandable:	-
Stackable:	-

Application methods

	Brush	
Thinner (%)	-	
Viscosity	ready to use	
Coverage per coat (g/sqm)	50 – 80	
Coats	2-3	



Annotations/Instructions for use

- Stir well before use!
- Provide for adequate ventilation!
- Do not paint outdoor woodwork in damp weather or under direct sunlight.
- We recommend painting in the direction of the wood grain.
- Polishing the surface with a cotton cloth after the application increases its brilliance.
- Clean soaked cloths immediately after use or submerge in water (danger of spontaneous combustion).
- The surface must be absolutely dry and free of dirt, oil, grease and sanding dust.

Application technology

Example	Dacha, Walnut glaze	
1. Gradual sanding	Grit size 80-100	
2. Glazing	OLI-FINISH Holzlasur Walnut, 50-80 g/sqm	
3. Drying at 23°C / 65% rel. humidity	Dust-dry	Overcoatable
	3 h	over night
4. Intermediate sanding	Grit size 150-180	
5. Glazing	OLI-FINISH Holzlasur Walnut, 50-80 g/sqm	
5. Drying at 23°C / 65% rel. humidity	Dust-dry	Overcoatable
	3 h	over night
6. Glazing	OLI-FINISH Holzlasur Walnut, 50-80 g/sqm	
7. Drying at 23°C / 65% rel. humidity	Dust-dry	
	3 h	

Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Last update: 12.02.2010.