



## OLI-NATURA HS Coloröl / HS Colour Oil

OLI-NATURA HS Colour Oil is a pigmented, deeply penetrating high solid oil made of modified natural resins and quickly drying oils with which you can treat and colour new wooden floors as well as those in need of restoration in a natural way and with only one application. The micro-sized, lightfast pigments penetrate into the topmost pores of the wood and give the surface a long-lasting, water and dirt resistant colouration. The wood is still able to breathe, which has a positive effect on the room climate. Depending on the colour shade you can achieve a rustic or an exotic look. For more glazing effects you may add OLI-NATURA HS Professional Oil. Seven transparent, UV stable and intermixable colours are available, which can be overcoated with OLI-AQUA TOP 2c Parquet sealer 51.20, when required.

### Properties

- suitable for nearly all wood types
- can be used for impregnating and as a primer
- colours can be intermixed
- easy application, by machine and manually
- extremely economical
- anti-skid
- highly wear-resistant
- partially repaintable
- absolutely natural, produces a healthy room climate
- Giscode Ö 40

### Test Standards

- in compliance with the EU Decopaint Directive
- DIN EN 71-3 (toy safety)
- free of formaldehyde and aromatic compounds
- free of biocidal substances and preservatives

### Areas of application

For the coloured basic treatment of untreated wooden, cork and OSB floors in the interior.

### Ordering information

OLI-NATURA HS Colour Oil

Colours	Lime white	710 019 02
	Grey	710 020 08
	Teak	710 021 04
	Mahogany	710 022 00
	Walnut	710 023 07
	Padouk	710 024 03
	Wenge	710 025 18

Other colours on request.

Container sizes 5 / 1 ltrs

### Composition

Modified plant oils such as linseed oil; isoparaffinic hydrocarbon of pharmaceutical quality; lead-free drying agents; lightfast soil and mineral pigments.

### Shelf-life/Storage

Shelf-life in factory sealed containers: 24 months. Storage and transport temperatures must not exceed +30°C.

### Labelling

For labelling details and safety instructions please refer to our safety datasheet at [www.oli-natura.de](http://www.oli-natura.de).

### Application

#### Application by roller or brush:


1. No matter if you want to treat an old or new floor, sand the wood gradually with grit sizes 80/100/120. The surface has to be clean, dry and free of grease, oil, wax and dust. A general exception is the colour *lime white* where you should do the final sanding with grit size 80.
2. Stir/shake the oil well before use and pour it carefully on the surface. Depending on the absorbency of the wood, the coverage per coat is approx. 20 g/sqm on oak, and up to 40 g/sqm on highly absorbent woods. Then spread it thinly and evenly with a brush, spatula or a mohair roller. Always work in sections on large areas.
3. Leave the oil to penetrate for 20 to 30 minutes. If necessary, pour additional oil on those areas where it has been absorbed faster. Then rub it in by using a rotary floor machine with a green application pad until the surface is saturated and no longer appears wet. Remove surplus oil with a squeegee.
4. After a drying time of 4 to 6 hours, do a final polishing with a rotary floor machine and white pad or a cotton cloth.
5. Depending on the air humidity and the temperatures, the floor can be exposed to normal wear after 2 to 3 days. Protect the surface from water during this time.

### Annotations

- Do not apply at floor temperatures below +12°C.
- Drying data refer to measurements under everyday conditions of +20°C and 50% humidity.
- Sand damaged areas well and apply one oil coat!
- Danger of spontaneous combustion! Clean the cloths/pads immediately after use or submerge in water.
- As a priming oil it can be overcoated with OLI-AQUA TOP 2c Parquet sealer 51.20. It can be overcoated after a drying time of 48 hours. Before overcoating, roughen the surface slightly with a rotary floor machine and green pad.
- The overcoating is done in full system. For further information please refer to the technical datasheet of the respective finishing laquers.

### After-treatment and care

Use OLI-NATURA HS Colour Oil, mixed at a ratio of 1:1 with OLI-NATURA Oil Thinner, for reconditioning to have a care product of the same colour. For common maintenance cleaning we recommend OLI-NATURA Wood Soap.

 Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Date: December 2009.



## OLI-NATURA HS Colour Oil **Polar white**

The pigmented OLI-NATURA HS Colour Oil Polar white, made of natural resins and quickly drying oils, is ideal for the design oriented coloured treatment of wooden floors. After only one application, the micro-sized, lightfast white pigments produce an extremely water-repellent, dirt proof and beautifully natural coat. The wood is open to diffusion and breathable, which has a positive effect on the room climate.

By brushing the surface, you can achieve particularly striking effects. The result: rustic white areas between soft growth rings and the face sides of the wood. Optionally, **Polar white** can be overcoated with OLI-AQUA TOP 2c Parquet sealer 51.20.

### Properties

- suitable for nearly all wood types
- can be used for impregnating and as a primer
- colours can be intermixed
- easy application, by machine and manually
- extremely economical
- anti-skid
- highly wear-resistant
- partially repaintable
- absolutely natural, produces a healthy room climate
- Giscode Ö 40

### Test Standards

- in compliance with the EU Decopaint Directive
- DIN EN 71-3 (toy safety)
- free of formaldehyde and aromatic compounds
- free of biocidal substances and preservatives

### Areas of application

For the coloured basic treatment of untreated wooden, cork and OSB floors in the interior.

### Bestellhinweis

OLI-NATURA HS Colour Oil Polar white 710 037 05

Container sizes 5 / 1 litres

### Composition

Modified plant oils such as linseed oil; isoparaffinic hydrocarbon of pharmaceutical quality; lead-free drying agents; lightfast soil and mineral pigments.

### Shelf-life/Storage

Shelf-life in factory sealed containers: 24 months. Storage and transport temperatures must not exceed +30°C.

### Labelling

For labelling details and safety instructions please refer to our safety datasheet at [www.oli-natura.de](http://www.oli-natura.de).

### Application

#### Application by roller or brush:

1. Sand the wood gradually with grit sizes 80/100. The surface has to be clean, dry and free of grease, oil, wax and dust.
2. Stir/shake the oil well before use and pour it carefully on the surface (approx. 20-30 g/sqm). Then rub it in with a brush or rotary floor machine with white pad until the surface is saturated and no longer appears wet. Alternatively, you can apply the material with a spatula. Always work in sections on large areas.
3. Depending on the humidity and the temperatures, the floor can be exposed to normal wear after 2 to 3 days. Protect the surface from water during this time.

#### Annotations

- Do not apply at floor temperatures below +12°C.
- Drying data refer to measurements under everyday conditions of +20°C and 50% humidity.
- Sand damaged areas well and apply one oil coat!
- Danger of spontaneous combustion! Clean the cloths/pads immediately after use or submerge in water.
- As a priming oil it can be overcoated with OLI-AQUA TOP Parquet sealer 51.20. It can be overcoated after a drying time of 48 hours. Before overcoating, roughen the surface slightly with a rotary floor machine and green pad.
- The overcoating is done in full system. For further information please refer to the technical datasheet of the respective finishing laquers.

#### After-treatment and care

OLI-NATURA Project Oil *lime white* is best suitable for reconditioning. For common maintenance cleaning we recommend OLI-NATURA Wood Soap.

**i** Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Date: December 2009.