



## OLI-NATURA Hartwachsöl / Hard Wax Oil

OLI-NATURA Hard Wax Oil is a special oil and wax combination for the surface treatment of interior woodwork. While the oil penetrates deeply into the wood, the wax remains on the surface producing a silk matt shine, which can be further intensified by polishing. The surface thus consolidated is easy to maintain, and resistant to dirt and water. As the pores of the wood are not sealed, the wood is still able to breathe.

### Properties

- suitable for nearly all wood types
- easy application, by machine and manually
- impregnates and protects
- anti-skid
- water repellent
- comfortable room climate
- partially repaintable
- Giscode Ö 60

### Test Standards

- in compliance with the EU Decopaint Directive
- DIN 531160 (saliva and sweat proof)
- DIN EN 71-3 (toy safety)
- free of formaldehyde and aromatic compounds
- free of biocidal substances and preservatives

### Areas of application

For the basic treatment of untreated wooden, cork and OSB floors as well as interior stairs, doors and worktops.

### Ordering information

OLI-NATURA Hard Wax Oil 710 009 18  
Container sizes 3 / 1 ltrs

### Composition

Modified plant oils and waxes, such as linseed oil and carnauba wax; disaromatized hydrocarbons; lead-free drying agents.

### Shelf-life/Storage

Shelf-life in factory sealed containers: 12 months. Storage and transport temperatures must not exceed +30°C.

### Labelling

For labelling details and safety instructions please refer to our safety datasheet at [www.oli-natura.de](http://www.oli-natura.de).

### Application

#### Application by roller or brush:

1. Sand the wood gradually with grit sizes 80/100/120. The surface must be clean, dry and free of grease, oil, wax and dust. With wooden floors we recommend you to fill the joints with OLI Joint filler and sanding powder before the final sanding.
2. Work fractionally on large areas, stir or shake the Hard Wax Oil well and pour it carefully on the surface. Depending on the absorbency of the wood, the coverage is approx. 40-50 g/sqm. Then spread thinly and evenly with a broad brush, spatula or a mohair roller.
3. Leave the Hard Wax Oil to penetrate for 20 to 30 minutes. If necessary, pour additional oil on those areas where it has been absorbed faster. Then rub it in by brush or by using a single-disc machine with a beige or white pad until the surface no longer appears wet. Remove surplus Hard Wax Oil with a squeegee or cotton cloth.
4. After a drying time of 6 to 8 hours, repeat the application as described in steps 2 and 3.
5. Depending on the humidity and the temperatures, the oil is fully hardened after 2 to 3 days. Protect the surface from water during this time.

### Annotations

- Do not apply at floor temperatures below +12°C.
- Drying data refer to measurements under everyday conditions of +20°C and 50% humidity.
- Sand damaged areas well and apply 1-2 coats of Hard Wax Oil.
- Danger of spontaneous combustion! Clean the cloths/pads immediately after use or submerge in water.

### After-treatment and care

Use OLI-NATURA Care Wax for first care and reconditioning. For common maintenance cleaning we recommend OLI-NATURA Wood Soap.

ⓘ Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Date: February 2008.