



## OLI-NATURA Yacht & Teaköl / Yacht & Teak Oil

OLI-NATURA Yacht & Teak Oil is our universal oil for outdoor use with a highly effective long term UV resistance, especially for the weatherproof treatment and care of yacht decks, verandas, pool surroundings and garden furniture made of hard or exotic wood types as well as pressure and vacuum impregnated softwood. The oil produces a hardwearing surface and highlights the natural colour and grain of the wood. The product is easy to apply and penetrates deeply. The oil blocks UV light effectively and protects the wood from turning grey or brittle.

### Properties

- easy application
- high and long-term protection against UV light
- highly weatherproof and moisture-regulating
- suitable for hardwood and exotic woods as well as pressure impregnated softwood
- impregnates and protects

### Test Standards

- in compliance with the EU Decopaint Directive
- DIN EN 71-3 (toy safety)
- free of formaldehyde and aromatic compounds
- free of biocidal substances and preservatives

### Areas of application

For the basic treatment and care of all common hardwood types outdoors, such as yacht decks, verandas, pool surroundings and garden furniture.

### Ordering information

OLI-NATURA Yacht & Teak Oil

Colours	Nature	710 032 03
	Teak	710 033 18
	Silver grey	710 034 06

Container sizes 3 / 1 ltrs

### Composition

Modified plant oils such as linseed oil; isoparaffinic hydrocarbon of pharmaceutical quality; lead-free drying agents, lightfast soil and mineral pigments, micronised titan oxide.

### Shelf-life/Storage

Shelf-life in factory sealed containers: 12 months. Storage and transport temperatures must not exceed +30°C.

### Labelling

For labelling details and safety instructions please refer to our safety datasheet at [www.oli-natura.de](http://www.oli-natura.de).

### Application

#### Application by roller or brush:


1. The wood must be clean, dry and free of grease. If you have weathered wood, we recommend an initial cleaning with OLI-NATURA Outdoor Cleaner. If necessary, sand down fibres that are sticking out or rough areas with fine sand paper (grit size 220).
2. Stir/shake the oil well before use and pour it carefully on the surface (approx. 40-80 g/sqm, depending on the absorbency of the wood). Spread it thinly and evenly with a brush along the wood grain, starting with the cross-section area of the wood.
3. After a drying time of 20 minutes, remove surplus oil with a cotton cloth. Take care that no oil residue remains visibly on the surface! If the wood is weathered or very dry, repeat the application.
4. In order to consolidate and increase the durability of the surface, you may polish it with a white pad.
5. Depending on the air humidity and the temperatures, the treated wood is touch-dry after 1 to 2 hours and fully hardened after 2 to 3 days. Protect the surface from water during this time.

### Annotations

- Drying data refer to measurements under everyday conditions of +20°C and 50% humidity.
- Do not paint wooden objects outdoors in damp weather or under direct sunlight.
- Sand damaged areas well and apply 1-2 oil coats!
- Danger of spontaneous combustion! Clean soaked cloths/pads immediately after use or submerge in water.

### After-treatment and care

Use OLI-NATURA Yacht & Teak Oil for reconditioning and care two times a year or as required. For maintenance cleaning we recommend OLI-NATURA Outdoor Cleaner.

 Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Date: February 2008.