

# OLI Universalgrund 1.50

## Universal primer 1.50



### Product description

Non-film-forming, highly insulating, spiritous one-component primer for roller application on ingredient-rich exotic woods and aged flooring with wax residues.

### Properties

- in compliance with the EU Decopaint Directive
- deep penetration
- low viscosity
- mild odour
- side-bonding minimizing
- neutral towards wax residues
- Giscode G2

### Areas of application

Safe basic priming of aged flooring, where the danger of wax residues persists even after sanding, and for the insulation of exotic wood types. Due to its low level of side-bonding, it is also suitable for the priming of delicate floors such as strip flooring, floorboards, etc.

### Ordering information

OLI Universalgrund 1.50 350 001 01  
Container sizes 10 / 3 ltrs

### Binder

Combination of synthetics

### Shelf-life/Storage

12 months in the factory sealed containers. Storage and transport temperatures are not to exceed +30°C.

### Labelling

For labelling details and safety instructions, please refer to our safety datasheet at [www.oli-lacke.de](http://www.oli-lacke.de).

### Annotations/Instructions for use

- Apply 1-2 coats of OLI Universal primer 1.50 by roller or brush, approx. 100 g/sqm.
- For a safe insulation against wax residues, we recommend the application of a third coat, if necessary.
- Do not use at floor temperature below +15°C.

### Pretreatment

Before priming, do a final sanding with grit size 120. The finer the sanding, the lesser the wood roughens up. The surface must be dry, thoroughly cleaned and free of oil, wax and grease.

### Application

#### 1 Priming



OLI Universal primer 1.50, approx. 100 g/sqm



30 min

### Drying

Figures above refer to normal conditions of +20°C and 50% relative humidity.