



# OLI-AQUA Grund 15.81

## - Primer -

### Product description

Excellently filling water-based one-component primer for roller application minimizing side-bonding, with a discreet colour intensification and good bonding. Can be combined with all OLI-AQUA parquet sealers.

### Properties

- in compliance with the EU Decopaint Directive
- highly elastic
- nearly no side-bonding
- minimizes the raising of the wood grain
- safe basic primer for delicate floors
- Giscode W3+

### Areas of application

Safe basic primer for delicate floors such as e.g. strip flooring, floorboards or parquet flooring on underfloor heating.

### Bestellhinweis

OLI-AQUA Grund 15.81				
- Primer -				
Gloss level	--			
Ordering code	420 915 07			
Container sizes	10/ 5 / 1 ltrs			

### Binder

Dispersion of synthetics (acrylate)

### Shelf-life/Storage

12 months in factory sealed containers. Storage and transport temperatures must not exceed +30°C or fall below +5°C.

### Labelling

For labelling details and safety instructions, please refer to our safety datasheet at [www.oli-lacke.de](http://www.oli-lacke.de).

### Instructions for use

- Stir well before use!
- Do not pour the material on the ground; apply out of the container!
- An intermediate sanding is indispensable if the intermediate drying time exceeds 12 hrs.
- Do not apply at floor temperatures below +15°C.

### Surface pre-treatment

Gradual sanding with grit sizes 80/100/120. The finer the sanding, the lesser the wood roughens up. The surface must be dry, thoroughly cleaned and free of oil, wax, grease, silicon and sanding dust.

### Application

1. Priming	Minimizing side-bonding		
	OLI-AQUA Primer 15.81, approx. 100 g/sqm		
	approx. 2-3 hrs		

### Drying

Figures above refer to normal conditions of +20°C and 50% relative humidity.

Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Date: 17 Dec.2009.