OLI-AQUA CLEAN Parkettgrundreiniger 15.97
Basic parquet cleaner 15.97

Product description
Solvent-free basic cleaner for post-construction cleaning as well as for heavily soiled wooden and parquet floors for which common wiping care products are not sufficient anymore. Removes old cleaner residues and polymer films reliably.

Properties
- gentle intensive cleaner for sealed and oiled parquet, wooden and cork floors
- removes extremely tenacious dirt and old cleaner residues reliably
- mild odour
- compatible with the OLI-AQUA polish series for parquet care (CARE, POLISH, POLISH*sport*)
- Giscode GG 20

Areas of application
All types of sealed, oiled and waxed parquet and cork floors.

Ordering information

OLI-AQUA CLEAN Parkettgrundreiniger 15.97	919 902 18
Container sizes	5 / 1 ltrs

Shelf-life/Storage
12 months in the factory sealed containers. Storage and transport temperatures are not to exceed +30°C or to fall below +5°C.

Labelling
For labelling details and safety instructions please refer to our safety data sheet at www.oli-lacke.de.

Annotations/Instructions for use
- Remove loose dirt by sweeping or vaccuum cleaning.
- On sealed floors: apply OLI-AQUA CLEAN15.97 with a broad wetmop; avoid "ponding".
- Remove the cleaner film after a residence time of approx. 10 min with a light-coloured pad; use a single-disc machine on larger areas.
- On oiled and waxed floors: Dilute OLI-AQUA CLEAN 15.97 with water at a ratio of 1:1 to 1:3 and start the cleaning immediately after the application of the cleaner dilution without previous residence time. Take up the entire dirt mass immediately with a water vacuum cleaner, in exceptional cases you may use absorbent, dry wetmops. Afterwards wipe the surface with clear water slightly damp with a well wrung-out mop.
- Always treat the floor in sections. If possible, the cleaning should be done by two persons, the first one etching the cleaner film, the second one suction cleaning the dirt mass immediately.
- Do not apply the cleaner dilution on sensitive surfaces (e.g. lacquered furniture, baseboards, doors).
- Check the surface to be cleaned in advance for cracks in the lacquer coat and open joints.
- Protect metal surfaces, expansion joints/transition profiles with adhesive tape before cleaning.
- Parquet and cork floors can absorb water at joints and thus change their shape due to swelling (especially beech coverings).
- A prolonged residence time of the cleaner on water-based sealing coats can result in temporary milky stains. Therefore, keep the residence time to the absolute minimum and never leave the floor wet over a longer period of time.

Application

❶ Lacquered surfaces

apply undiluted, thinly and evenly, approx. 15-30 ml/sqm

residence time approx. 10 min

loosen cleaner film residues with white pad

take up the dirt mass with a water vacuum cleaner or broad wetmop

wipe with clear water slightly damp with a well wrung-out mop

❷ Waxed/oiled surfaces

dilute the basic cleaner : water at a ratio of 1 : 3

spread thinly and evenly, approx. 15-30 ml/sqm

loosen cleaner film residues with white pad

take up the dirt mass with a water vacuum cleaner or broad wetmop

wipe with clear water slightly damp with a well wrung-out mop

Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Date: November 2008

OLI Lacke GmbH · Bahnhofstr. 22, D-09244 Lichtenau · Phone +49(0)37208/ 84-0, Fax +49(0)37208/ 84-382 · www.oli-lacke.de