



OLI-AQUA DOMO Parquet sealer 15.40

Product description

Highly aesthetic one-component water-based sealer for wooden and parquet floors in domestic areas. The specific strengths of the product are its appealing look and the colour intensifying effect even on oak, beech and merbau. Moreover, this resistant and low-maintenance material is easy to apply without leaving brush marks. Small areas can be coated with spatula and sealed within one day!

Properties

- in compliance with the EU-Decopaint Directive
- pleasant colour intensifying effect
- easy application
- ultra quick complete system application
- highest resistance in 'home' areas
- extremely lightfast and highly transparent lacquer coat
- very good heel abrasion resistance
- Giscode W3+

Test standards

- DIN EN 71-3 (toy safety)
- DIN 53160 (sweat and saliva proof)
- DIN 68861 T1 B, C (chemical resistance)
- DIN 68861 T4 (scratch resistance)
- free of formaldehyde and aromatic compounds
- NMP and NEP free
- not combustible in liquid state

Areas of application

Private areas, such as dining rooms, bedrooms and living rooms.

Ordering information

OLI-AQUA DOMO Parquet sealer 15.40				
Gloss levels	Matt	Semi matt		
Bestell-Code	420 973 00	420 972 04		
Container sizes	5 / 1 ltrs	5 / 1 ltrs		

Binder

Acrylate polymer

Shelf-life/Storage

12 months in factory sealed containers. Storage and transport temperatures must not exceed +30°C or fall below +5°C.

Labelling

For labelling details and safety instructions, please refer to our safety data sheet at www.oli-lacke.de.

Annotations/Instructions for use

- Stir well before use!
- Do not pour the material on the ground; apply out of the container!
- Due to the strong colour intensifying effect, use spatula only when applying DOMO also as top coat. Do not use spatula on delicate wood types, such as beech, maple or ash; use a roller.
- An intermediate sanding is absolutely necessary if the intermediate drying time exceeds 12 hrs.
- Do not apply at a floor temperature below +15°C.

Surface pretreatment

Gradual sanding with grit sizes 80/100/120. The finer the sanding, the lesser the wood roughens up. The surface must be dry, thoroughly cleaned and free of oil, wax, grease, silicon and sanding dust.



Application

1. Priming	A) multi-coat application	B) side-bonding minimizing setup	C) efficient basic setup with spatula
	OLI-AQUA DOMO approx. 100 g/sqm	OLI-AQUA Primer 15.81, approx. 100 g/sqm	
			OLI-AQUA DOMO, 1-2 cross-coats, 20-40 g/sqm each
	approx. 2-3 hrs	approx. 2-3 hrs	approx. 20 min
2. Sealing	1. coat		
	OLI-AQUA DOMO, approx. 100 g/sqm		
	over night		
	intermediate sanding, grit size 120-150		
3. Sealing	2. coat		
	OLI-AQUA DOMO, approx. 100 g/sqm		
	approx. 5-6 hrs		
	Exposure to normal wear after 8-10 days		

Drying

Figures above refer to normal conditions of +20°C and 50% relative humidity.

Care

For maintenance cleaning and care we recommend the use of our high-quality OLI-AQUA Polish series (CARE, POLISH, CLEAN).

Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Date: 17 Dec.2009.