



OLI-AQUA Exotengrund

Primer for exotic woods

Product description

Excellently insulating water-based one-component primer for roller application on ingredient-rich exotic woods. Also suitable for aged flooring due to its outstanding seal-off effect against wax residues.

Properties

- in compliance with the EU Decopaint Directive
- excellent seal-off effect
- strong bonding agent
- intensification of the wood colour
- high-build
- Giscode W2+

Areas of application

Ingredient-rich exotic and highly resinous woods, where there can be adhesion problems and the risk of "yellow effloresces" over the time. Can be overcoated with all OLI-AQUA parquet sealers.

Ordering information

OLI-AQUA Exotengrund 430 008 06
Container sizes 5 litres

Binder

Acrylic resin

Shelf-life/Storage

6 months in the factory sealed containers. Storage and transport temperatures are not to exceed + 30 °C or to fall below + 5 °C.

Labelling

For labelling details and safety instructions please refer to our safety data sheet at www.oli-lacke.de.

Annotations/Instructions for use

- Shake or stir well before use!
- Apply one coat of OLI-AQUA primer for exotic woods thickly with roller; approx. 100 g/sqm.
- The priming coat can be overcoated without intermediate sanding with all OLI-AQUA parquet sealers, except OLI-AQUA ECONOMY parquet sealer 15.52.
- OLI-AQUA primer for exotic woods should not be poured on the floor, but applied out of the container.
- Do not apply at a floor temperature below + 15°C.

Pretreatment

Before priming, do a final sanding with grit size 120. The finer the sanding, the lesser the wood roughens up. The surface must be dry, thoroughly cleaned and free of oil, wax and grease.

Application

1 Priming



OLI-AQUA primer for exotic woods, approx. 100 g/sqm



5-6 hrs

Drying

Figures above refer to normal conditions of 20°C and 50% relative humidity.