



OLI-AQUA FIX FILL Fugenkittlösung

Joint filler

Product description

OLI-AQUA FIX FILL is an eco-friendly, water-based solution for filling joints of wooden and parquet floors.

Properties

- in compliance with the EU Decopaint Directive
- easy application
- good filling properties
- excellent sanding properties
- very quick drying
- very little shrinkage
- good bonding in the joints
- Giscode W1

Areas of application

Suitable for all common wood types, preferably for floors that will subsequently be coated with water-based OLI-AQUA parquet sealers. Not suitable for surfaces that ought to be painted in colour with OLI-FloorColor. In this case we recommend the use of OLI joint filler 5.50.

Ordering information

OLI-AQUA FIX FILL Fugenkittlösung 410 008 02
Container sizes 5 / 1 litres

Shelf-life/Storage

12 months in the factory sealed containers. Storage and transport temperatures are not to exceed + 30 °C or to fall below + 5 °C.

Labelling

For labelling details and safety instructions please refer to our safety data sheet at www.oli-lacke.de.

Annotations/Instructions for use





- Shake or stir well before use!
- Prepare a homogeneous paste of OLI AQUA FIX FILL with sanding powder (wood flour) ready for filling joints. Apply the mixture on the entire parquet floor with a stainless steel spatula before the final sanding. After drying, do a final sanding. Clean the floor thoroughly and remove dust before priming.
- Note! The wood flour used must be clean, i.e. free of lacquer and wax residues. The filling paste ought to fill the joints to full depth. If the paste is too dry, the joints are only filled cursorily and will be laid bare again after the subsequent sanding.

Pretreatment

Do a rough and semi-finish sanding of the floor. Remove dust thoroughly from the surface. The sanding dust of the semi-finish sanding is well suitable for preparing the filling paste with the putty solution.

Application

1 Joint filling

-  Prepare a paste of OLI-AQUA FIX FILL with sanding dust
-  Fill the joints to full depth with putty/paste
-  approx. 45 min
-  Sanding, grit size 120

Drying

Figures above refer to normal conditions of 20°C and 50% relative humidity.

