



OLI-FloorColor Kolorierungssystem

Colouration system

Product description

OLI-FloorColor makes your individual design dreams come true. With this colouration system, wooden and parquet floors can be coloured with striking effects. Whether trendy, noble or exotic, OLI-FloorColor sets the tone. We offer 10 standard colours that can be intermixed. Further colours are available on request.

Can be overcoated with OLI-AQUA STANDARD, OLI-AQUA BUSINESS or OLI-AQUA TOP.

Properties

- in compliance with the EU Decopaint Directive
- Ready-to-use
- intermixable colours
- good light-fastness

Areas of application

For the renovation of aged floors in order to give them a "new look" or for the latest trends in home decoration in which expensive exotic wood types can be imitated in a cost-effective way. Fully bonded parquet flooring is best suitable for this product.

Ordering information

Colours	Wenge	325 100 18
	Ebony	325 102 02
	Padouk	325 109 07
	Rosewood	325 103 09
	Mahogany	325 104 05
	Smoky oak	325 105 01
	Walnut	325 101 06
	Cherry	325 106 08
	Teak	325 107 04
	Doussie	325 108 00
	Lightener	325 111 09

Container sizes 1 litre

Labelling

For labelling details and safety instructions please refer to our safety data sheet at www.oli-lacke.de.

Annotations/Instructions for use

- Shake or stir well before use!
- If you need more than one container, please pour contents of all containers together before use and stir well in order to avoid potential colour differences between the containers.
- Application with roller, brush or spatula. Depending on the absorbency of the wood, the coverage with roller or brush is approx. 100 g/sqm and with spatula approx. 60 g/sqm. Wood humidity < 12%, a room temperature of 15-25°C and a relative humidity of 50% have to be maintained.
- The colouration of coniferous wood is not recommended due to sanding marks and varying absorbency.
- Apply OLI-FloorColor evenly thin avoiding brush marks. Rub it in immediately with a single-disc machine and white pad. No intermediate sanding on OLI-FloorColor! Can be overcoated after complete drying over night. Delicate floors, e.g. floorboards, wood plaster, strip flooring, parquet on underfloor heating, have to be sealed with OLI-AQUA FLEX parquet sealer in order to avoid cracking.

Pretreatment

Gradual sanding with grit sizes 80/100/120. The finer the sanding, the lesser the wood roughens up. Before the final sanding process, fill the joints with OLI joint filler 5.50 and sanding powder. The surface must be dry, thoroughly cleaned and free of oil, wax, grease, silicon and sanding dust.

Application

1 Colouration



OLI-FloorColor, approx. 100 g/sqm



spread excess material with white pad



approx. 12 hrs

2 Priming



A) Delicate floors
OLI-AQUA primer 15.81, approx. 100 g/sqm

B) Alternatively
OLI-AQUA STANDARD, BUSINESS or TOP parquet sealer, approx. 100 g/sqm



approx. 2-3 hrs

3 Sealing (1. coat)



OLI-AQUA STANDARD, BUSINESS or TOP parquet sealer, approx. 130 g/sqm



approx. 5-6 hrs



sanding, grit size 120-150

4 Sealing (2. coat)



OLI-AQUA STANDARD, BUSINESS or TOP parquet sealer, approx. 130 g/sqm



approx. 5-6 hrs



Fully hardened after 8-10 days

Drying

Figures above refer to normal conditions of 20°C and 50% relative humidity.

Care

For maintenance cleaning and care we recommend the use of our high-quality OLI-AQUA Polish series.