



OLI-KS Spielfeldmarkierungsfarbe

Line marking paint

Product description

Synthetic resin based colour lacquer system for line marking on sports floors.

Properties

- in compliance with the EU Decopaint Directive
- opaque, brilliant colour shades
- easy application by brush, gauze or foam roller
- good levelling
- excellent bonding
- Giscode KH 1

Areas of application

Line marking on sports floors that are sealed with OLI-KS parquet sealer 7400 matt, KS 7600 semi matt or KS 7800 glossy.

Ordering information

Colours	yellow	800 759 03
	red	800 760 09
	blue	800 765 00
	green	800 761 05
	orange	800 764 04
	white	800 762 01
	black	800 763 08
Container sizes	1 litre	
Thinner	V 110	912 601 00

Binder

High-quality modified synthetic resin

Shelf-life/Storage

6 months in the factory sealed containers. Storage and transport temperatures are not to exceed +30°C.

Labelling

For labelling details and safety instructions please refer to our safety data sheet at www.oli-lacke.de.

Annotations/Instructions for use

- Shake or stir well before use!
- Application with roller or brush.
- Coverage is approx. 100-120 running metres per litre.
- Do not use at a floor temperature below +15C.
- Delineation of the lines to paint with adequate adhesive tape. The tape must have a strong adhesion to avoid the lacquer from spreading under it. Remove the adhesive tape after 20 minutes of drying.
- One coat is generally sufficient. With light colour shades you may apply a second coat after 30 minutes.
- Note! An additional lacquer coat of OLI-KS parquet sealer is absolutely necessary!
- Danger of spontaneous combustion! Clean soaked cloths/pads immediately after use or submerge in water.

Pretreatment

Gradual sanding with grit sizes 100/120. The surface must be dry, thoroughly cleaned and free of oil, wax, grease, silicon and sanding dust.

Application

1 Priming



OLI-KS parquet sealer, approx. 100-120 g/sqm



approx. 18 hrs



Sanding, grit size 120-150

2 Line marking



OLI-KS line marking paint

Remove adhesive tape after approx. 20 min



approx. 18 hrs

3 Sealing (1. coat)



OLI-KS parquet sealer, approx. 100-120 g/sqm



approx. 18 hrs

4 Sealing (2. coat)



OLI-KS parquet sealer, approx. 100-120 g/sqm



approx. 18 hrs



Fully hardened after 8-10 days

Drying

Figures above refer to normal conditions of 20°C and 50% relative humidity.

Care

For maintenance cleaning and care we recommend the use of our high-quality OLI-AQUA Polish series.

