

# OLI-AQUA POLISH Parkettgrundpflege 15.95

## Basic parquet care 15.95



### Product description

Solvent-free parquet care product for initial care and reconditioning of all waterproof sealed wooden and parquet floors. Maintains and protects the newly sealed floor against scratches and walking marks and should be carried out after each basic cleaning. While OLI-AQUA POLISH 15.95 matt gives the floor a silk matt look, OLI-AQUA POLISH 15.95 glossy is ideal for parquet flooring with a shiny finishing coat.

### Properties

- initial care and reconditioning of sealed wooden and parquet floors
- reliable protection against walking marks and scratches
- on request matt or glossy look
- compatible with OLI-AQUA CARE Parquet wiping care 15.94
- Giscode GE10

### Areas of application

Care of all waterproof sealed wooden and parquet floors.

### Ordering information

OLI-AQUA POLISH Parkettgrundpflege 15.95		
Gloss level	matt	420 904 08
	glossy	420 903 01
Container sizes	5 / 1 ltrs	

### Binder

Waxy polymer dispersion

### Shelf-life/Storage

12 months in the factory sealed containers. Storage and transport temperatures are not to exceed +30°C or to fall below +5°C.

### Labelling

For labelling details and safety instructions, please refer to our safety datasheet at [www.oli-lacke.de](http://www.oli-lacke.de).

### Instructions for use

- Apply OLI-AQUA POLISH Basic parquet care 15.95 undiluted in an evenly thin film with a lint-free broad wetmop on the thoroughly cleaned floor. If you want to obtain a higher gloss level, repeat the application in cross direction when the film is touch-dry.
- Before exposing the floor to normal use, allow to dry for at least 12 hrs or, ideally, over night.
- Coverage: 20-25 g/sqm per coat.
- OLI-AQUA POLISH Basic parquet care 15.95 glossy highlights the natural wood grain and is colour intensifying. In general, this is a desirable effect, but in case of doubt you should do a test application in a corner area.

### Application

#### 1 Basic care



apply undiluted, thinly and evenly, approx. 20-25 ml/sqm



allow to dry



for a higher gloss level, repeat the application



overnight drying