

General information

Depending on the intensity of use, a floor's finish is subject to a natural wearout. Therefore, regular care according to DIN 18356 is an absolute necessity. When the surface has become defective due to heavy wear, it must be sanded and resealed. Applying a sealing finish is an artisan work. This means that small disruptions may occur on the surface (e.g. dust particles). However, this does not have any influence on the floor's durability. Wood is a natural product. It expands, contracts, and permanently adapts to the surrounding humidity and room climate. During the heating period, the relative air humidity decreases significantly. The wood reacts to this condition and releases humidity itself - it starts contracting. This is visible by joint/gap building in the parquet floor. The longer and the more intensely rooms are heated, the dryer the air and the wider the joints in the floor. The broadest joints are therefore to be expected towards the end of the heating period. At the end of summer they are generally most narrow or closed again. In order to counteract joint/gap building to a certain extent, you may attach evaporators to the radiators or have a number of foliage plants in your house. For a comfortable room climate and the prevention of large dimensional changes of the wood, a consistent temperature of about 20°C and a relative air humidity of 55-65% are recommended.

- Newly sealed floors must be allowed to dry up to 24 hours before use. Please arrange furniture carefully, and do not push it.
- Leave your newly sealed floor at least 10 days time before you expose it to its normal wear, and before using care products!
- Do not use steel splints or sharp cleaning pads.
- Dirt and sand have a sandpaper effect and are to be removed immediately.
- For cleaning and care do only use high-quality products that are compatible with each other.
- By providing dirt collection zones in front of the entrance, you can reduce floor soiling significantly.
- In order to prevent scratches, you may attach small pieces of felt under your furniture. If you have furniture with rollers, protect the floor with floor mats.
- If you use skid-reducing under-carpet mats, take care that they do not contain any softeners.



Your floor was sealed on the: _____

with: _____

Dealer/Signature

Oli Lacke GmbH

Bahnhofstr. 22 | 09244 Lichtenau / Germany
Tel. +49 (0) 37208/84-0 | Fax +49 (0) 37208/84-382
info@oli-lacke.de | www.oli-lacke.de



Care instructions for wood floors sealed according to DIN 18356



DE_Pflegeanweisung für versiegelte Holzfussböden_ST_28072015



Care and cleaning intervals

Wear intensity	Basic care and reconditioning	Maintenance	Basic cleaning
normal/ medium (living rooms and bedrooms)	10 days after sealing, every 3 months for reconditioning and after each basic cleaning	weekly	every 12 months
high (corridors, offices)	10 days after sealing, monthly for reconditioning and after each basic cleaning	every 2 days	every 6 months
intensive (multi-purpose halls, shops, restaurants, schools)	10 days after sealing, monthly for reconditioning and after each basic cleaning	daily	every 3 months
gymnasiums and sports halls	10 days after sealing and after each basic cleaning with OLI-AQUA POLISHsport 15.96 sports floor care	depending on the wear intensity with OLI-AQUA POLISHsport 15.96 sports floor care	as necessary

First of all, the floor must be cleaned dry (e.g. with a broom or vacuum cleaner with a brush). Do a wet cleaning afterwards. Take care not to leave any puddles due to the danger of wood swelling. Do only mop the floor slightly damp, i.e. with a well wrung-out cloth or mop.

OLI-AQUA POLISH 15.95 Basic parquet care Primary care and reconditioning



Primary care should be conducted not earlier than 10 days after the sealing, and after each basic cleaning. OLI-AQUA POLISH 15.95 Basic parquet care protects the wood floor from walking marks and scratches. While OLI-AQUA POLISH 15.95 Basic parquet care glossy gives the parquet a satin finished look, OLI-AQUA POLISH 15.95 Basic parquet care matt gives it a silk matt-finished one.

Apply OLI-AQUA POLISH 15.95 Basic parquet care undiluted, thinly and evenly with a lint-free broad wetmop or cotton cloth. Allow the floor to dry for at least 12 hours before use. If you wish a higher gloss level, repeat the application in cross direction as soon as the coat is touch-dry. Do not polish! Coverage: approx. 20-25g/sqm per coat.


OLI-AQUA POLISHsport 15.96 Sports floor care Sports floor care



For the maintenance and care of gymnasium floors we recommend you to use OLI-AQUA POLISHsport 15.96 Sports floor care. This product is certified in compliance with DIN 18032-2; it is skid-resistant, increases the floor's wear-resistance and removes abrasion marks reliably. OLI-AQUA POLISHsport 15.96 Sports floor care is a multi-purpose product and can thus be used for basic care as well as for wipe care (diluted).

Basic care: Apply the product undiluted, thinly and evenly with a lint-free broad wetmop on the thoroughly cleaned floor. Repeat the application after a drying time of approx. 20-30 minutes. Coverage: 15-30 ml/sqm. **Wipe care:** Add one part of OLI-AQUA POLISHsport 15.96 Sports floor care to 10 parts of water and mop the floor slightly damp with this dilution.

OLI-AQUA CARE 15.94 Parquet wipe care Maintenance



For maintenance care we recommend you to use OLI-AQUA CARE 15.94 Parquet wipe care. This product removes dirt and grease reliably. Add approx. 50 ml OLI-AQUA CARE 15.94 Parquet wipe care to 10 litres of clear water and wipe the floor slightly damp with a wrung-out mop, sponge or cloth. For the removal of grease spots, heel abrasion marks and other stubborn sorts of dirt, apply OLI-AQUA CARE 15.94 Parquet wipe care undiluted with a scratch-free white pad and then take up the dirt and cleaner residues with a wrung-out cloth.

OLI-AQUA CLEAN 15.97 Basic parquet cleaner Basic cleaning



For extremely pertinacious sorts of dirt and cleaner residues that cannot be removed by common wipe care anymore, we recommend our soft intensive cleaner OLI-AQUA CLEAN 15.97 Basic parquet cleaner. Apply OLI-AQUA CLEAN 15.97 Basic parquet cleaner undiluted with a lint-free broad wetmop. After a residence time of approx. 10 minutes, take up etched dirt and cleaner residues with a water Hoover or a dry mop. Wipe the floor slightly damp with clear water afterwards. A basic cleaning should be carried out as seldom as possible.