



# PRESS RELEASE

January 31<sup>th</sup> 2019

## AUTHENTIC OPTICS AND HAPTICS

With »OLI-AQUA AUTHENTIC 51.30 I 2c-Parquet Sealer« comes a new raw-wood-effect on wooden floors in 2019.

**No other parquet sealer has been as strikingly inconspicuous as the »OLI-AQUA AUTHENTIC«. The surface is impressive with ultra matt effects without changing on the colour of the wood. The floor is »invisibly« protected and shows hardly any difference to the raw wood. And anyone who touches it understands: the raw wood effect surface emphasises the high value of the parquet.**

"With the product name »OLI-AQUA AUTHENTIC« we are alluding to the properties of the parquet seal to give the floor an amazingly authentic raw wood look," says Managing Director Götz Schubert. The two-component parquet sealer does not change the colour of the wood at all and shows optically or haptically hardly any lacquer coat. The surface scores with mechanical robustness and with a gloss level of less than 5% it is exceptionally matt. Thanks to considerable progress in the field of aqueous polyurethane dispersions, it was possible to optimally integrate the matting agent into the molecular structure of the paint binder. The matting agent scatters the light so that the dull matt effect is further enhanced. The surface is extremely resistant to dust and fingerprints. It is also resistant to yellowing and much more scratch-resistant than many comparable parquet finishes. The puristic elegance appeals particularly to design-oriented people who want an amazingly natural seal for their parquet floor.

### Easy to process

In principle, the application of the »OLI-AQUA AUTHENTIC« does not differ from that of a conventional two-component parquet sealer. Immediately before application, the Parquet Sealer has to be mixed with »OLI-AQUA Hardener 13.2« in a ratio of 20:1. The pot life of 3 hours is also practical for large surfaces. The sealer has a very good filling capacity and can be applied evenly in three roller coats with 100 g/m<sup>2</sup> each. In order to achieve a perfect surface result, an intermediate sanding should be carried out before applying the last sealing coat. After complete curing, the water-based parquet sealer forms a dense film with a very high surface hardness. This makes the wood extremely resistant to mechanical influences and moisture penetration. This is why the seal can even be used on heavily frequented parquet floors in commercial areas such as restaurants, kindergartens and schools. It is particularly suitable for oak and light-color soft- and hard woods for indoors.

### Very environmentally friendly

With a VOC-content of less than 3% is »OLI-AQUA AUTHENTIC« very environmentally friendly and ensures a healthy living environment. The water-based parquet sealer conforms to EU-Decopaint-directives and is a building product approved by the German Institute for Building Technology (DIBt). The product complies with the latest state of coating technology and environmental legislation and



complies with DIN EN 71-3 (safety of toys) and is saliva- and perspiration-resistant in accordance with DIN 53160.

### Easy-to-maintain

Dust or loose dirt is simply removed with a broom, vacuum cleaner or a dry mop. Sticky dirt can be removed quickly with the parquet wipe care »OLI-AQUA CARE 15.94«. Simply add some wipe care to the water, wipe the surface with a damp cloth and allow to dry - done. For initial care and for the refreshment, we recommend »OLI-AQUA POLISH 15.95« in »Matt«, which is applied undiluted and as an evenly thin film to the thoroughly cleaned floor, applying with a wiping weasel or a wide mop.

**Video:** [https://www.youtube.com/watch?v=d\\_gzA2HsETw&t=3s](https://www.youtube.com/watch?v=d_gzA2HsETw&t=3s)

VIDEO Authentic



**Pictures:** see attachment



© 2019 Oli Lacke GmbH

**Title:** Discover now: The new 2C-Parquet Sealer OLI-AQUA AUTHENTIC 51-30 with raw wood effect!



**Title:** By scanning of the QR code on the label the user can access the technical information and the safety data sheet with his smartphone.



**Title:** Mix OLI-AQUA AUTHENTIC 2c Parquet sealer 51.30 immediately before use at a ratio of 20:1 with OLI-AQUA hardener 13.2.



© 2019 Oli Lacke GmbH

**Title:** The parquet sealer has a very good filling capacity and can be applied evenly in three coats with 100 g/m<sup>2</sup> per layer.



© 2019 Oli Lacke GmbH

**Title:** The floor is "invisibly" protected and is exceptionally matt with a gloss level of less than 5%.

---

**ABOUT US:** Oli Lacke GmbH is a future-oriented German company that develops, produces and sells ecological high-quality lacquers, stains, oils and waxes for the professional sector. The core competences of our company are modern lacquers for the entire range of craftsman-made and semi-industrial wooden interiors. The OLI-NATURA Oils & Waxes Trademark was launched in 1997. Today, the NATURA section is producing a full range of natural oils and waxes for crafted woodwork as well as for the industrial sector. With these strong brands for surface protection, Oli offers a full range of products for the professional trade, craftsmen and the industrial sector.





**CONTACT:** Oli Lacke GmbH | Bahnhofstr. 22 | 09244 Lichtenau, Germany

Phone: +49 (0) 37208 / 84-0 | Fax: +49 (0) 37208 / 84-382 | e-Mail: [info@oli-lacke.de](mailto:info@oli-lacke.de) | web: [www.oli-lacke.de](http://www.oli-lacke.de)