

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-FINISH Holzlasur

Print date: 18.05.2016

Product code: A01355

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

OLI-FINISH Holzlasur

Further trade names

OLI-FINISH Holzlasur
fungizidfrei
diverse Farbtöne

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Colour

1.3. Details of the supplier of the safety data sheet

Company name:	Oli Lacke GmbH	
Street:	Bahnhofstrase 22	
Place:	D-09244 Lichtenau	
Telephone:	+49(0)37208/84200	Telefax: +49(0)37208/84268
e-mail:	entwicklung@oli-lacke.de	
Internet:	www.oli-lacke.de	

1.4. Emergency telephone number:

Gemeins. Gifinformationszentrum Erfurt
+49(0)361/730730

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
Flammable liquid: Flam. Liq. 3
Specific target organ toxicity - single exposure: STOT SE 3
Aspiration hazard: Asp. Tox. 1
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Flammable liquid and vapour.
May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Lösungsmittelnaphtha leicht, Benzolgehalt < 0,1 Gew. %
Lösungsmittelnaphtha, niedrig siedend (Benzolgehalt < 0,1 Gew.%)
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha
Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

Signal word: Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-FINISH Holzlasur

Print date: 18.05.2016

Product code: A01355

Page 2 of 9

H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH208	Contains 2-Butanonoxim (vgl. Ethylmethylketoxim), Co-bis(2-Ethylhexanoat) . May produce an allergic reaction.
--------	---

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Gemisch aus nachfolgend aufgeführten Stoffen mit ungefährlichen Beimengungen:

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-95-6	Lösungsmittelnaphtha leicht, Benzolgehalt < 0,1 Gew. %			70 - < 75 %
	265-199-0		01-2119455851-35	
	STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H336 H304 H411			
1330-20-7	xylene			1 - < 5 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H312 H332 H315			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			< 1 %
	265-151-9		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
22464-99-9	2-Ethylhexansäure, Zirconiumsalz			< 1 %
	245-018-1		01-2119979088-21	
	Repr. 2; H361d			
96-29-7	2-butanone oxime, ethyl methyl ketone oxime, ethyl methyl ketoxime			< 1 %
	202-496-6	616-014-00-0		
	Carc. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1; H351 H312 H318 H317			
136-52-7	Cobaltbis(2-ethylhexanoat)			< 1 %
	205-250-6		01-2119524678-29	
	Repr. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H361f H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-FINISH Holzlasur

Print date: 18.05.2016

Product code: A01355

Page 3 of 9

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After contact with eyes

Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Impaired consciousness

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a doctor.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam. Carbon dioxide (CO₂). Extinguishing powder. Water mist

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Hazardous decomposition products: carbon black Danger of serious damage to health by prolonged exposure. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. - No smoking. Provide adequate ventilation. In case of fire and/or explosion do not breathe fumes. Safe handling: see section 7 Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Observe in addition any national regulations! In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-FINISH Holzlasur

Print date: 18.05.2016

Product code: A01355

Page 4 of 9

6.4. Reference to other sections

See chapter 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Even after use and until complete evaporation of the flammable components, there is still a danger of an explosive steam-air mixture forming. Only use the material in places where open light, fire and other flammable sources can be kept away. Take precautionary measures against static discharge. Use explosion-proof electrical equipment. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles When using do not eat, drink or smoke. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Concentrated vapours are heavier than air. Vapours may form explosive mixtures with air.

Further information on handling

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

Observe in addition any national regulations!

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Betriebssicherheitsverordnung (BetrSichV)

Advice on storage compatibility

Von stark sauren oder alkalischen Materialien oder Oxidationsmitteln fernhalten.

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place. Keep away from heat. Notice the directions for use on the label. Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition. - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-FINISH Holzlasur

Print date: 18.05.2016

Product code: A01355

Page 5 of 9

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

8.2. Exposure controls**Appropriate engineering controls**

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Protective and hygiene measures

Wash hands before breaks and after work. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Use protective skin cream before handling the product.

Skin protection

Protective clothing: Natural fibres (e.g. cotton) heat-resistant synthetic fibres

Respiratory protection

During spraying wear suitable respiratory equipment. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
Colour:

Test method**Changes in the physical state**

Flash point:	> 23 °C	DIN EN ISO 1523
Lower explosion limits:	0,7 vol. %	
Upper explosion limits:	8 vol. %	
Ignition temperature:	450 °C	
Vapour pressure: (at 20 °C)	10 hPa	
Density (at 20 °C):	0,83 g/cm ³	ISO 2811
Flow time: (at 20 °C)	verarbeitungsfertig	
Solvent separation test:	< 3 %	
Solvent content:	79 %	

9.2. Other information

Solid content: 21 %

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-FINISH Holzlasur

Print date: 18.05.2016

Product code: A01355

Page 6 of 9

SECTION 10: Stability and reactivity

10.1. Reactivity

refer to chapter 7. No further action is necessary.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reactions with: Alkalis (alkalis), concentrated. Acid, concentrated. Oxidizing agents, strong.

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapours.

10.5. Incompatible materials

Rubber articles

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
1330-20-7	xylene			
	dermal	ATE 1100 mg/kg		
	inhalative vapour	ATE 11 mg/l		
	inhalative aerosol	ATE 1,5 mg/l		
96-29-7	2-butanone oxime, ethyl methyl ketone oxime, ethyl methyl ketoxime			
	dermal	ATE 1100 mg/kg		

Carcinogenic/mutagenic/toxic effects for reproduction

The components in this formulation do not meet the criteria for classification as CMR category 1 or 2.

Additional information on tests

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Practical experience

Observations relevant to classification

In case of inhalation

Adverse human health effects and symptoms :May cause respiratory irritation. May cause damage to liver if inhaled. May cause damage to kidneys if inhaled. Central nervous system depression - Dizziness, Headache, Drowsiness, Unconsciousness

After eye contact:

Irritating to eyes.

In case of ingestion :

Vomiting , Gastrointestinal complaints

After skin contact:

The product is skin resorptive. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

SECTION 12: Ecological information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-FINISH Holzlasur

Print date: 18.05.2016

Product code: A01355

Page 7 of 9

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
96-29-7	2-butanone oxime, ethyl methyl ketone oxime, ethyl methyl ketoxime				
	Acute crustacea toxicity	EC50	750 mg/l	48 h	Daphnia magna

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
96-29-7	2-butanone oxime, ethyl methyl ketone oxime, ethyl methyl ketoxime	0,63

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances
Classified as hazardous waste.

Waste disposal number of used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances
Classified as hazardous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-FINISH Holzlasur

Print date: 18.05.2016

Product code: A01355

Page 8 of 9

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Special Provisions:	163 640E 650
Limited quantity:	5 L
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Special Provisions:	163 640E 650
Limited quantity:	5 L

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	163, 223, 955
Limited quantity:	5 L
EmS:	F-E, S-E

Air transport (ICAO)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	A3 A72
Limited quantity Passenger:	10 L
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

Other applicable information (air transport)

Passenger-LQ: Y344

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-FINISH Holzlasur

Print date: 18.05.2016

Product code: A01355

Page 9 of 9

E1

00000000005: Y344

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

14.6. Special precautions for user

refer to chapter 7. No further action is necessary.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 656 g/l

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 2-Butanonoxim (vgl. Ethylmethylketoxim), Co-bis(2-Ethylhexanoat) . May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)