Telefax: +49(0)37208/84268

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-NATURA Yacht & Teaköl

Print date: 12.03.2015 Product code: A01397 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

OLI-NATURA Yacht & Teaköl

Further trade names

OLI-NATURA Yacht & Teaköl

farblos/ eingefärbt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Colour

1.3. Details of the supplier of the safety data sheet

Company name: Oli Lacke GmbH
Street: Bahnhofstrase 22
Place: D-09244 Lichtenau
Telephone: +49(0)37208/84200

e-mail: entwicklung@oli-lacke.de

Internet: www.oli-lacke.de

1.4. Emergency telephone Gemeins. Gifinformationszentrum Erfurt

number: +49(0)361/730730

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

R phrases:

Repeated exposure may cause skin dryness or cracking.

GHS classification

This mixture is not classified as hazardous according to Regulation (EC) No. 1272/2008.

2.2. Label elements

Hazardous components which must be listed on the label

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

Precautionary statements

P273 Avoid release to the environment.

Special labelling of certain mixtures

EUH208 Contains 2-butanone oxime, ethyl methyl ketone oxime, ethyl methyl ketoxime,

Cobaltbis(2-ethylhexanoat). May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Gemisch aus nachfolgend aufgeführten Stoffen mit ungefährlichen Beimengungen:

according to Regulation (EC) No 1907/2006

OLI-NATURA Yacht & Teaköl

Print date: 12.03.2015 Product code: A01397 Page 2 of 8

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
292-460-6	Isopar L (Xn)	40 - < 45 %
90622-58-5	Xn - Harmful R65-66	
	Asp. Tox. 1; H304	
265-150-3	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	1 - < 5 %
64742-48-9	Xn - Harmful R65	
649-327-00-6	Asp. Tox. 1; H304	
245-018-1	Zirkonium(2-ethylhexanoat)	< 1 %
22464-99-9	Repr. Cat. 3 R63	
	Repr. 2; H361d	
01-2119979088-21		
202-496-6	2-butanone oxime, ethyl methyl ketone oxime, ethyl methyl ketoxime	< 1 %
96-29-7	Carc. Cat. 3, Xn - Harmful, Xi - Irritant R40-21-41-43	
616-014-00-0	Carc. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1; H351 H312 H318 H317	
286-272-3	Zink(2-ethylhexanoat), basisch	< 1 %
85203-81-2	Xi - Irritant, N - Dangerous for the environment R38-51/53	
205-250-6	Cobaltbis(2-ethylhexanoat)	< 1 %
136-52-7	Repr. Cat. 3, N - Dangerous for the environment R62-43-50-53	
	Eye Irrit. 2, Skin Sens. 1, Repr. 2, Aquatic Acute 1, Aquatic Chronic 1; H319 H317 H361f H400 H410	
01-2119524678-29		7
		-

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After contact with eyes

Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious)

according to Regulation (EC) No 1907/2006

OLI-NATURA Yacht & Teaköl

Print date: 12.03.2015 Product code: A01397 Page 3 of 8

and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Impaired consciousness

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a doctor.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam. Carbon dioxide (CO2). Extinguishing powder. Water mist

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Hazardous decomposition products: carbon black Danger of serious damage to health by prolonged exposure. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. - No smoking. Provide adequate ventilation. In case of fire and/or explosion do not breathe fumes. Safe handling: see section 7 Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Observe in addition any national regulations! In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

See chapter 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Even after use and until complete evaporation of the flammable components, there is still a danger of an explosive steam-air mixture forming. Only use the material in places where open light, fire and other flammable sources can be kept away. Take precautionary measures against static discharge. Use explosion-proof electrical equipment. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools. Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles When using do not eat, drink or smoke. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Concentrated vapours are heavier than air. Vapours may form explosive mixtures with air.

according to Regulation (EC) No 1907/2006

OLI-NATURA Yacht & Teaköl

Print date: 12.03.2015 Product code: A01397 Page 4 of 8

Further information on handling

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

Observe in addition any national regulations!

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Betriebssicherheitsverordnung (BetrSichV)

Advice on storage compatibility

Von stark sauren oder alkalischen Materialien oder Oxidationsmitteln fernhalten.

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place. Keep away from heat. Notice the directions for use on the label. Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition. - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Protective and hygiene measures

Wash hands before breaks and after work. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Use protective skin cream before handling the product.

Skin protection

Protective clothing: Natural fibres (e.g. cotton) heat-resistant synthetic fibres

Respiratory protection

During spraying wear suitable respiratory equipment. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

Do not allow to enter into surface water or drains

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour:

Test method

Changes in the physical state

according to Regulation (EC) No 1907/2006

OLI-NATURA Yacht & Teaköl						
Print date: 12.03.2015	Product code: A01397	Page 5 of 8				
Flash point:	> 60 °C	DIN EN ISO 1523				
Lower explosion limits: Upper explosion limits:	0,6 vol. % 7 vol. %					
Ignition temperature:	240 °C					
Vapour pressure: (at 20 °C)	3 hPa					
Density (at 20 °C): Flow time: (at 20 °C)	0,875 g/cm³ verarbeitungsfertig	ISO 2811				
Solvent separation test: Solvent content:	< 3 % 41,5 %					
9.2. Other information						

SECTION 10: Stability and reactivity

10.1. Reactivity

Solid content:

refer to chapter 7. No further action is necessary.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reactions with: Alkalis (alkalis), concentrated. Acid, concentrated. Oxidizing agents, strong.

58.5 %

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapours.

10.5. Incompatible materials

Rubber articles

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
96-29-7	2-butanone oxime, ethyl methyl ketone oxime, ethyl methyl ketoxime				
	dermal	ATE	1100 mg/kg		

Carcinogenic/mutagenic/toxic effects for reproduction

The components in this formulation do not meet the criteria for classification as CMR category 1 or 2.

Additional information on tests

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Practical experience

Observations relevant to classification

In case of inhalation

Adverse human health effects and symptoms :May cause respiratory irritation. May cause damage to

according to Regulation (EC) No 1907/2006

OLI-NATURA Yacht & Teaköl

Print date: 12.03.2015 Product code: A01397 Page 6 of 8

liver if inhaled. May cause damage to kidneys if inhaled. Central nervous system depression -

Dizziness, Headache, Drowsiness, Unconsciousness

After eye contact:

Irritating to eyes.

In case of ingestion:

Vomiting, Gastrointestinal complaints

After skin contact:

The product is skin resorptive. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
96-29-7	2-butanone oxime, ethyl methyl ketone oxime, ethyl methyl ketoxime					
	Acute crustacea toxicity	EC50	750 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
96-29-7	2-butanone oxime, ethyl methyl ketone oxime, ethyl methyl ketoxime	0,63

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic

solvents or other dangerous substances

Classified as hazardous waste.

Waste disposal number of used product

according to Regulation (EC) No 1907/2006

OLI-NATURA Yacht & Teaköl

Print date: 12.03.2015 Product code: A01397 Page 7 of 8

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS;

wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic

solvents or other dangerous substances

Classified as hazardous waste.

Waste disposal number of contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic

solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

Other applicable information (land transport)

No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

Other applicable information (marine transport)

No dangerous good in sense of these transport regulations.

Air transport (ICAO)

Other applicable information (air transport)

No dangerous good in sense of these transport regulations.

14.6. Special precautions for user

refer to chapter 7. No further action is necessary.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 363 g/l

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

21 Harmful in contact with skin.

38 Irritating to skin.

40 Limited evidence of a carcinogenic effect.

41 Risk of serious damage to eyes.

according to Regulation (EC) No 1907/2006

OLI-NATURA Yacht & Teaköl				
Print date: 12.03.201		Page 8 of 8		
43	May cause sensitisation by skin contact.			
50	Very toxic to aquatic organisms.			
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.			
53	May cause long-term adverse effects in the aquatic environment.			
62	Possible risk of impaired fertility.			
63	Possible risk of harm to the unborn child.			
65	Harmful: may cause lung damage if swallowed.			
66	Repeated exposure may cause skin dryness or cracking.			
Full text of H stat	ements referred to under Sections 2 and 3			
H304	May be fatal if swallowed and enters airways.			
H312	Harmful in contact with skin.			
H317	May cause an allergic skin reaction.			
H318	Causes serious eye damage.			
H319	Causes serious eye irritation.			
H351	Suspected of causing cancer.			
H361d	Suspected of damaging the unborn child.			
H361f	Suspected of damaging fertility.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
Further Information	on			

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The

information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid

for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)