

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Print date: 16.03.2015

Product code: A00706

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

OLI-AQUA TOP 2K Parkettsiegel 51.20

Further trade names

OLI-AQUA TOP
2K Parkettsiegel 51.20
diverse Glanzgrade

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Colour

1.3. Details of the supplier of the safety data sheet

Company name:	Oli Lacke GmbH	
Street:	Bahnhofstrasse 22	
Place:	D-09244 Lichtenau	
Telephone:	+49(0)37208/84200	Telefax: +49(0)37208/84268
e-mail:	entwicklung@oli-lacke.de	
Internet:	www.oli-lacke.de	

1.4. Emergency telephone number:

Gemeins. Gifinformationszentrum Erfurt
+49(0)361/730730

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This mixture is not classified as hazardous according to Directive 1999/45/EC.

GHS classification

This mixture is not classified as hazardous according to Regulation (EC) No. 1272/2008.

2.2. Label elements

Precautionary statements

P404	Store in a closed container.
P235+P410	Keep cool. Protect from sunlight.
P273	Avoid release to the environment.

Special labelling of certain mixtures

EUH208	Contains 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one, Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.
--------	---

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Print date: 16.03.2015

Product code: A00706

Page 2 of 8

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
203-961-6	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	1 - < 5 %
112-34-5	Xi - Irritant R36	
603-096-00-8	Eye Irrit. 2; H319	

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.
 Never give anything by mouth to an unconscious person or a person with cramps.
 If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
 If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.
 After contact with skin, wash immediately with plenty of water and soap.
 Do not wash with: Solvents/Thinner

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do.
 Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
 Call a physician immediately.
 Put victim at rest, cover with a blanket and keep warm.
 Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Impaired consciousness

4.3. Indication of any immediate medical attention and special treatment needed

Call a physician immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.
 Hazardous decomposition products: carbon black. Danger of serious damage to health by prolonged exposure.
 Use appropriate respiratory protection.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Print date: 16.03.2015

Product code: A00706

Page 3 of 8

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Contains: Solvent - Keep away from sources of ignition. - No smoking. Ventilate affected area.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Safe handling: see section 7
Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Collect in closed and suitable containers for disposal. Disposal: see section 13
Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

See chapter 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Contains: Solvent - In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof electrical equipment.

Never use pressure to empty container. Keep/Store only in original container. Do not allow to enter into surface water or drains. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV)

Advice on storage compatibility

Do not store together with: Oxidising agent, Strong acid, Strong alkali

Further information on storage conditions

Notice the directions for use on the label.
storage temperature of °C 5 up to °C 30
Contains: Solvent - Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight.
Keep away from sources of ignition. - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Print date: 16.03.2015

Product code: A00706

Page 4 of 8

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Eye/face protection

Wear eye/face protection.

Hand protection

Wear suitable gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. See information supplied by the manufacturer.

Suitable material: NBR (Nitrile rubber).

Use protective skin cream before handling the product.

Skin protection

Wear anti-static footwear and clothing (Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.

Use suitable breathing apparatus.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour:

pH-Value (at 20 °C):

7 - 9

Changes in the physical state

Initial boiling point and boiling range:

100 °C

Flash point:

> 60 °C DIN EN ISO 1523

Lower explosion limits:

0,8 vol. %

Upper explosion limits:

5,9 vol. %

Ignition temperature:

204 °C

Vapour pressure:

31,6 hPa

(at 20 °C)

Test method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Print date: 16.03.2015

Product code: A00706

Page 5 of 8

Density (at 20 °C): 1,05 g/cm³ ISO 2811
 Flow time: verarbeitungsfertig
 (at 20 °C)
 Solvent separation test: < 3 %
 Solvent content: 4 %

9.2. Other information

Solid content: 32 %

SECTION 10: Stability and reactivity

10.1. Reactivity

refer to chapter 7. No further action is necessary.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent, Strong acid, Strong alkali

10.4. Conditions to avoid

In case of warming: Formation of: Hazardous decomposition products

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO₂), Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether				
	oral	LD50	5660 mg/kg	Rat	
	dermal	LD50	4120 mg/kg	Rabbit	

Practical experience

Observations relevant to classification

Following inhalation:

Adverse human health effects and symptoms: May cause respiratory irritation. May cause damage to liver if inhaled. May cause damage to kidneys if inhaled. Central nervous system depression.

Symptoms: Headache, Dizziness, Drowsiness, Unconsciousness

After eye contact:

Irritating to eyes. (reversible.)

Following skin contact:

The product is skin resorptive. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Further information

There are no data available on the mixture itself.

The classification was carried out according to the calculation method of the Preparations Directive

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Print date: 16.03.2015

Product code: A00706

Page 6 of 8

(1999/45/EC).

Reference to other sections: 2, 3

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether					
	Acute algae toxicity	ErC50	> 100 mg/l		Scenedesmus sp.	
	Acute crustacea toxicity	EC50	> 100 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	0,56 (25°C)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

There are no data available on the mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains.
Dispose according to legislation.

Waste disposal number of waste from residues/unused products

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Waste disposal number of used product

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Waste disposal number of contaminated packaging

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Print date: 16.03.2015

Product code: A00706

Page 8 of 8

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)