

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA Metallgrund 210.35

Revision date: 29.03.2019

Product code: A01920

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

OLI-AQUA Metallgrund 210.35

Further trade names

OLI-AQUA Metallgrund
rotbraun und schwarz

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Colour

1.3. Details of the supplier of the safety data sheet

Company name:	Oli Lacke GmbH	
Street:	Bahnhofstrasse 22	
Place:	D-09244 Lichtenau	
Telephone:	+49(0)37208/84200	Telefax: +49(0)37208/84268
e-mail:	entwicklung@oli-lacke.de	
Internet:	www.oli-lacke.de	

1.4. Emergency telephone number:

Gemeins. Gifinformationszentrum Erfurt
+49(0)361/730730

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Hazardous to the aquatic environment: Aquatic Acute 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Zinkphosphat

Signal word: Warning

Pictograms:



Hazard statements

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P391 Collect spillage.

P102 Keep out of reach of children.

Special labelling of certain mixtures

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA Metallgrund 210.35

Revision date: 29.03.2019

Product code: A01920

Page 2 of 9

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
7779-90-0	trizinc bis(orthophosphate)			5 - < 10 %
	231-944-3	030-011-00-6		
	Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1; H400 H410			
14807-96-6	Talkum			5 - < 10 %
	238-877-9			
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether			5 - < 10 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H312 H302 H315 H319			
1314-13-2	Zinkoxid			1 - < 5 %
	215-222-5			
	Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1; H400 H410			
2634-33-5	1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one			< 0.1 %
	220-120-9	613-088-00-6		
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1; H302 H315 H318 H317 H400			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.

After contact with skin, wash immediately with plenty of water and soap.

Do not wash with: Solvents/Thinner

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Call a physician immediately.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA Metallgrund 210.35

Revision date: 29.03.2019

Product code: A01920

Page 3 of 9

Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Impaired consciousness

4.3. Indication of any immediate medical attention and special treatment needed

Call a physician immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous decomposition products: carbon black. Danger of serious damage to health by prolonged exposure.

Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Contains: Solvent - Keep away from sources of ignition - No smoking. Ventilate affected area.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Safe handling: see section 7

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal. Disposal: see section 13

Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

See section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Contains: Solvent - In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof electrical equipment.

Never use pressure to empty container. Keep/Store only in original container. Do not allow to enter into surface water or drains. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA Metallgrund 210.35

Revision date: 29.03.2019

Product code: A01920

Page 4 of 9

Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV)

Advice on storage compatibility

Do not store together with: Oxidising agent, Strong acid, Strong alkali

Further information on storage conditions

Notice the directions for use on the label.

storage temperature of °C 5 up to °C 30

Contains: Solvent - Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid	240 mmol/mol	urine	Post shift

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Eye/face protection

Wear eye/face protection.

Hand protection

Wear suitable gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. See information supplied by the manufacturer.

Suitable material: NBR (Nitrile rubber).

Use protective skin cream before handling the product.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA Metallgrund 210.35

Revision date: 29.03.2019

Product code: A01920

Page 5 of 9

Skin protection

Wear anti-static footwear and clothing (Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.

Use suitable breathing apparatus.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour:

Test method

Changes in the physical state

Flash point: > 60 °C DIN EN ISO 1523

Lower explosion limits: 1,1 vol. %

Upper explosion limits: 10,6 vol. %

Ignition temperature: 240 °C

Vapour pressure:
(at 20 °C) 1,2 hPa

Density (at 20 °C): 1,25 g/cm³ ISO 2811

Flow time:
(at 20 °C) verarbeitungsfertig

Solvent separation test: < 3 %

Solvent content: 8 %

9.2. Other information

Solid content: 51 %

SECTION 10: Stability and reactivity

10.1. Reactivity

refer to chapter 7. No further action is necessary.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent, Strong acid, Strong alkali

10.4. Conditions to avoid

In case of warming: Formation of: Hazardous decomposition products

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO₂), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA Metallgrund 210.35

Revision date: 29.03.2019

Product code: A01920

Page 6 of 9

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether				
	oral	LD50 mg/kg	470	Rat	
	dermal	ATE mg/kg	1100		
	inhalative vapour	ATE	11 mg/l		
	inhalative aerosol	ATE	1,5 mg/l		
1314-13-2	Zinkoxid				
	oral	LD50 mg/kg	7950	Maus	
	inhalative aerosol	LC50	2500 mg/l	Maus	
2634-33-5	1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one				
	oral	ATE mg/kg	500		

Further information

There are no data available on the mixture itself.

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Reference to other sections: 2, 3

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7779-90-0	trizinc bis(orthophosphate)					
	Acute fish toxicity	LC50 mg/l	0,09	96 h	Regenbogenforelle	
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether					
	Acute fish toxicity	LC50 mg/l	1490	96 h	Lepomis macrochirus	
1314-13-2	Zinkoxid					
	Acute fish toxicity	LC50	1,1 mg/l	96 h	Regenbogenforelle	
	Acute crustacea toxicity	EC50 mg/l	0,098	48 h	Großer Wasserfloh	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether	0,81 (25°C)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA Metallgrund 210.35

Revision date: 29.03.2019

Product code: A01920

Page 7 of 9

12.6. Other adverse effects

No data available

Further information

There are no data available on the mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains.
Dispose according to legislation.

Waste disposal number of waste from residues/unused products

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Waste disposal number of used product

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Waste disposal number of contaminated packaging

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Contaminated packaging

Completely emptied packages can be recycled.
Dispose according to legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 3082
<u>14.2. UN proper shipping name:</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Gefahrauslöser: Zinkphosphat
<u>14.3. Transport hazard class(es):</u>	9
<u>14.4. Packing group:</u>	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 601
Limited quantity:	5 L
Transport category:	3
Hazard No:	90
Tunnel restriction code:	E

Inland waterways transport (ADN)

<u>14.1. UN number:</u>	UN 3082
<u>14.2. UN proper shipping name:</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
<u>14.3. Transport hazard class(es):</u>	9
<u>14.4. Packing group:</u>	III

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA Metallgrund 210.35

Revision date: 29.03.2019

Product code: A01920

Page 8 of 9

Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 601
Limited quantity:	5 L

Marine transport (IMDG)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Special Provisions:	274, 335
Limited quantity:	5 L
EmS:	F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Special Provisions:	A97 A158
Limited quantity Passenger:	30 kg G
IATA-packing instructions - Passenger:	964
IATA-max. quantity - Passenger:	450 L
IATA-packing instructions - Cargo:	964
IATA-max. quantity - Cargo:	450 L

Other applicable information (air transport)

Passenger-LQ: Y964
E1
0000000005: Y964

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

14.6. Special precautions for user

refer to chapter 7. No further action is necessary.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 100 g/l

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA Metallgrund 210.35

Revision date: 29.03.2019

Product code: A01920

Page 9 of 9

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)