

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## OLI-EP 2K DS-Lackfarbe F 18251

Revision date: 01.10.2021

Product code: A01540

Page 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

OLI-EP 2K DS-Lackfarbe F 18251

#### Further trade names

OLI-EP  
2K Dickschichtfarbe F 18251/F 18254  
diverse Farbtöne

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Colour

#### 1.3. Details of the supplier of the safety data sheet

Company name:	Oli Lacke GmbH	
Street:	Bahnhofstrasse 22	
Place:	D-09244 Lichtenau	
Telephone:	+49(0)37208/84200	Telefax: +49(0)37208/84268
e-mail:	entwicklung@oli-lacke.de	
Internet:	www.oli-lacke.de	

#### 1.4. Emergency telephone number:

Gemeins. Gifinformationszentrum Erfurt  
+49(0)361/730730

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:  
Flammable liquid: Flam. Liq. 3  
Skin corrosion/irritation: Skin Irrit. 2  
Serious eye damage/eye irritation: Eye Dam. 1  
Respiratory or skin sensitisation: Skin Sens. 1  
Hazardous to the aquatic environment: Aquatic Chronic 2  
Hazard Statements:  
Flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye damage.  
May cause an allergic skin reaction.  
Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)  
Phenol, methylsterolysiert  
butan-1-ol; n-butanol

Signal word: Danger

##### Pictograms:



##### Hazard statements

H226 Flammable liquid and vapour.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**OLI-EP 2K DS-Lackfarbe F 18251**

Revision date: 01.10.2021

Product code: A01540

Page 2 of 11

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Special labelling of certain mixtures**

EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Contains epoxy constituents with an average molecular weight of 700.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-EP 2K DS-Lackfarbe F 18251

Revision date: 01.10.2021

Product code: A01540

Page 3 of 11

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)			20 - < 25 %
	500-033-5	603-074-00-8		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
68512-30-1	Phenol, methylsterolysiert			15 - < 20 %
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H317 H412			
1330-20-7	xylene			10 - < 15 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H226 H332 H312 H315 H319			
64742-95-6	Lösungsmittelnaphtha leicht, Benzolgehalt < 0,1 Gew. %			5 - < 10 %
	265-199-0		01-2119455851-35	
	STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H336 H304 H411			
71-36-3	butan-1-ol; n-butanol			1 - < 5 %
	200-751-6	603-004-00-6	01-2119484630-38	
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether			1 - < 5 %
	203-961-6	603-096-00-8	01-2119475104-44	
	Eye Irrit. 2; H319			
34590-94-8	Dipropylenglykolmonomethylether			1 - < 5 %
	252-104-2		01-2119450011-60	
100-41-4	ethylbenzene			< 0.1 %
	202-849-4	601-023-00-4	01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	20 - < 25 %
	Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100		
1330-20-7	215-535-7	xylene	10 - < 15 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg		
71-36-3	200-751-6	butan-1-ol; n-butanol	1 - < 5 %
	oral: ATE = 500 mg/kg		
112-34-5	203-961-6	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	1 - < 5 %
	dermal: LD50 = 4120 mg/kg; oral: LD50 = 5660 mg/kg		
100-41-4	202-849-4	ethylbenzene	< 0.1 %
	inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg		

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**OLI-EP 2K DS-Lackfarbe F 18251**

Revision date: 01.10.2021

Product code: A01540

Page 4 of 11

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

**After contact with skin**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

**After contact with eyes**

Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Impaired consciousness

**4.3. Indication of any immediate medical attention and special treatment needed**

Immediately call a doctor.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. Water mist

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Burning produces heavy smoke. Hazardous decomposition products: carbon black Danger of serious damage to health by prolonged exposure. Use appropriate respiratory protection.

**5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Keep away from sources of ignition - No smoking. Provide adequate ventilation. In case of fire and/or explosion do not breathe fumes. Safe handling: see section 7 Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Observe in addition any national regulations! In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**OLI-EP 2K DS-Lackfarbe F 18251**

Revision date: 01.10.2021

Product code: A01540

Page 5 of 11

**Other information**

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

**6.4. Reference to other sections**

See section 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Even after use and until complete evaporation of the flammable components, there is still a danger of an explosive steam-air mixture forming. Only use the material in places where open light, fire and other flammable sources can be kept away. Take precautionary measures against static discharges. Use explosion-proof electrical equipment. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing. Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

**Advice on protection against fire and explosion**

Concentrated vapours are heavier than air. Vapours may form explosive mixtures with air.

**Further information on handling**

Observe in addition any national regulations!

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Betriebssicherheitsverordnung (BetrSichV)

**Hints on joint storage**

Von stark sauren oder alkalischen Materialien oder Oxidationsmitteln fernhalten.

**Further information on storage conditions**

Keep only in the original container in a cool, well-ventilated place. Keep away from heat. Follow the instructions for use on the label. Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

**7.3. Specific end use(s)**

Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-EP 2K DS-Lackfarbe F 18251

Revision date: 01.10.2021

Product code: A01540

Page 6 of 11

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
34590-94-8	(2-methoxymethylethoxy) propanol	50	308		TWA (8 h)	WEL
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL
78-83-1	2-Methylpropan-1-ol	50	154		TWA (8 h)	WEL
		75	231		STEL (15 min)	WEL
71-36-3	Butan-1-ol	50	154		STEL (15 min)	WEL
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
12001-26-2	Mica, respirable	-	0.8		TWA (8 h)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

## 8.2. Exposure controls

### Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

### Protective and hygiene measures

Wash hands before breaks and after work. Do not eat, drink, smoke or sneeze at the workplace.

### Eye/face protection

Tightly sealed safety glasses.

### Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Use protective skin cream before handling the product.

### Skin protection

Protective clothing: Natural fibres (e.g. cotton) heat-resistant synthetic fibres

### Respiratory protection

During spraying wear suitable respiratory equipment. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

### Environmental exposure controls

Do not allow to enter into surface water or drains.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**OLI-EP 2K DS-Lackfarbe F 18251**

Revision date: 01.10.2021

Product code: A01540

Page 7 of 11

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: liquid  
 Colour:

**Test method****Changes in the physical state**

Boiling point or initial boiling point and boiling range:	98 °C	
Flash point:	> 23 °C	DIN EN ISO 1523
Lower explosion limits:	1,4 vol. %	
Upper explosion limits:	11,4 vol. %	
Auto-ignition temperature:	230 °C	
Vapour pressure: (at 20 °C)	9 hPa	
Density (at 20 °C):	1,34 g/cm <sup>3</sup>	ISO 2811
Flow time: (at 20 °C)	thixotrop	
Solvent separation test:	< 3%	
Solvent content:	26 %	
<b><u>9.2. Other information</u></b>		
Solid content:	74 %	

**SECTION 10: Stability and reactivity****10.1. Reactivity**

refer to chapter 7. No further action is necessary.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Exothermic reactions with: Alkalis (alkalis), concentrated. Acid, concentrated. Oxidizing agents, strong.

**10.4. Conditions to avoid**

Thermal decomposition can lead to the escape of irritating gases and vapours.

**10.5. Incompatible materials**

Rubber articles

**10.6. Hazardous decomposition products**

Carbon monoxide. Carbon dioxide. Nitrogen oxides (NO<sub>x</sub>).

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Acute toxicity, dermal.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-EP 2K DS-Lackfarbe F 18251

Revision date: 01.10.2021

Product code: A01540

Page 8 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
71-36-3	butan-1-ol; n-butanol				
	oral	ATE 500 mg/kg			
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether				
	oral	LD50 5660 mg/kg	Rat		
	dermal	LD50 4120 mg/kg	Rabbit		
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation aerosol	ATE 1,5 mg/l			

#### Irritation and corrosivity

Irritating to eyes. After skin contact: irritant.

#### Carcinogenic/mutagenic/toxic effects for reproduction

The components in this formulation do not meet the criteria for classification as CMR category 1 or 2.

#### Additional information on tests

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether					
	Acute algae toxicity	ErC50 > 100 mg/l		Scenedesmus sp.		
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna		
100-41-4	ethylbenzene					
	Acute algae toxicity	ErC50 3,6 mg/l	96 h		GESTIS	

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-EP 2K DS-Lackfarbe F 18251

Revision date: 01.10.2021

Product code: A01540

Page 9 of 11

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	0,56 (25°C)
100-41-4	ethylbenzene	3,15

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

#### 12.7. Other adverse effects

There are no data available on the preparation/mixture itself.

#### Further information

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains.

Dispose according to legislation.

##### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	Paint
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
Classification code:	F1
Special Provisions:	163 367 650
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-EP 2K DS-Lackfarbe F 18251

Revision date: 01.10.2021

Product code: A01540

Page 10 of 11

Hazard No: 30  
Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3  
Classification code: F1  
Special Provisions: 163 367 650  
Limited quantity: 5 L  
Excepted quantity: E1

#### Marine transport (IMDG)

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3  
Special Provisions: 163, 223, 367, 955  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3  
Special Provisions: A3 A72 A192  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

#### 14.6. Special precautions for user

refer to chapter 7. No further action is necessary.

#### 14.7. Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):  
Entry 3, Entry 28, Entry 55

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**OLI-EP 2K DS-Lackfarbe F 18251**

Revision date: 01.10.2021

Product code: A01540

Page 11 of 11

2010/75/EU (VOC): 348 g/l

**National regulatory information**

Water hazard class (D): 2 - obviously hazardous to water

**Additional information**

Observe in addition any national regulations!

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment is not required.

**SECTION 16: Other information****Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*