according to Regulation (EC) No 1907/2006

OLI-AQUA MODU B 18.35

Revision date: 01.10.2021	Product code: A00809		Page 1 of 9
	Floduct code. A00809		Fage 101
SECTION 1: Identification of t	he substance/mixture and of the company/u	undertaking	
1.1. Product identifier			
OLI-AQUA MODU B 18.	35		
Further trade names			
OLI-AQUA MODU B			
1K/2K Buntlack			
diverse Farbtöne			
1.2. Relevant identified uses of t	he substance or mixture and uses advised agair	<u>ist</u>	
Use of the substance/mixture			
Colour			
1.3. Details of the supplier of the	safety data sheet		
Company name:	Oli Lacke GmbH		
Street:	Bahnhofstrase 22		
Place:	D-09244 Lichtenau		
Telephone:	+49(0)37208/84200	Telefax:+49(0)37208/84268	
e-mail:	entwicklung@oli-lacke.de		
Internet:	www.oli-lacke.de		
1.4. Emergency telephone	Gemeins. Gifinformationszentrum Erfurt		
<u>number:</u>	+49(0)361/730730		
SECTION 2: Hazards identific	ation		
	uuun		

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements

P102

Regulation (EC) No. 1272/2008

Precautionary statements

Keep out of reach of children.

Special labelling of certain mixtures

	J	
EUH208		Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one,
		2-methylisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and
		2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210		Safety data sheet available on request.
EUH211		Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

according to Regulation (EC) No 1907/2006

OLI-AQUA MODU B 18.35

Revision date: 01.10.2021

Product code: A00809

Page 2 of 9

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification		·	
111-76-2	2-butoxyethanol, butyl cellosoly	ve, ethylene glycol monobutyl et	ner	5 - < 10 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 4, Acute Tox. 4, Acu	te Tox. 4, Skin Irrit. 2, Eye Irrit. 2	; H332 H312 H302 H315 H319	
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			< 0.1 %
	220-120-9	613-088-00-6		
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1; H302 H315 H318 H317 H400			
55965-84-9	reaction mass of 5-chloro-2-me	thyl-2H-isothiazol-3-one and 2-i	nethyl-2H-isothiazol-3-one (3:1)	< 0.1 %
	-	613-167-00-5		
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	z. Limits, M-factors and ATE	
111-76-2	203-905-0	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether	5 - < 10 %
		TE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = oral: LD50 = 470 mg/kg	
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	< 0.1 %
	oral: ATE = 5	00 mg/kg Skin Sens. 1; H317: >= 0,05 - 100	
55965-84-9	-	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	< 0.1 %
	50 mg/kg; ora	. M=100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Immediately remove any contaminated clothing, shoes or stockings. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

according to Regulation (EC) No 1907/2006

OLI-AQUA MODU B 18.35

Revision date: 01.10.2021

Product code: A00809

Page 3 of 9

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Call a physician immediately. Put victim at rest, cover with a blanket and keep warm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Impaired consciousness

4.3. Indication of any immediate medical attention and special treatment needed

Call a physician immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous decomposition products: carbon black. Danger of serious damage to health by prolonged exposure. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Contains: Solvent - Keep away from sources of ignition - No smoking. Ventilate affected area. Avoid breathing dust/fume/gas/mist/vapours/spray. Safe handling: see section 7 Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Disposal: see section 13 Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

See section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Contains: Solvent - In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof electrical equipment.

according to Regulation (EC) No 1907/2006

OLI-AQUA MODU B 18.35

Revision date: 01.10.2021

Product code: A00809

Page 4 of 9

Never use pressure to empty container. Keep/Store only in original container. Do not allow to enter into surface water or drains. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV)

Hints on joint storage

Do not store together with: Oxidising agent, Strong acid, Strong alkali

Further information on storage conditions

Follow the instructions for use on the label.

storage temperature of °C 5 up to °C 30

Contains: Solvent - Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
34590-94-8	(2-methoxymethylethoxy) propanol	50	308		TWA (8 h)	WEL
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
50-00-0	Formaldehyde	2	2.5		TWA (8 h)	WEL
		2	2.5		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol		Post shift

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Eye/face protection

Wear eye/face protection.

according to Regulation (EC) No 1907/2006

OLI-AQUA MODU B 18.35

Revision date: 01.10.2021

Product code: A00809

Page 5 of 9

Hand protection

Wear suitable gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. See information supplied by the manufacturer.

Suitable material: NBR (Nitrile rubber).

Use protective skin cream before handling the product.

Skin protection

Wear anti-static footwear and clothing (Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values. Use suitable breathing apparatus.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	liquid		
			Test method
Changes in the physical sta	ate		
Flash point:		> 60 °C	DIN EN ISO 1523
Lower explosion limits:		1,1 vol. %	
Upper explosion limits:		10,6 vol. %	
Auto-ignition temperature:		240 °C	
Vapour pressure: (at 20 °C)		31,6 hPa	
Density (at 20 °C):		1,04 g/cm ³	ISO 2811
Flow time: (at 20 °C)		verarbeitungsfertig	
Solvent separation test:		< 3 %	
Solvent content:		9,2 %	
9.2. Other information			
Solid content:		34,0 %	

SECTION 10: Stability and reactivity

10.1. Reactivity

refer to chapter 7. No further action is necessary.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent, Strong acid, Strong alkali

according to Regulation (EC) No 1907/2006

OLI-AQUA MODU B 18.35

Revision date: 01.10.2021

Product code: A00809

Page 6 of 9

10.4. Conditions to avoid

In case of warming: Formation of: Hazardous decomposition products

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO2), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
111-76-2	2-butoxyethanol, butyl ce	losolve, ethy	/lene glycol ı	nonobutyl ether		
	oral	LD50 mg/kg	470	Rat		
	dermal	ATE mg/kg	1100			
	inhalation vapour	ATE	11 mg/l			
	inhalation aerosol	ATE	1,5 mg/l			
2634-33-5	1,2-benzisothiazol-3(2H)-	one; 1,2-ber	nzisothiazolir	i-3-one		
	oral	ATE mg/kg	500			
55965-84-9	reaction mass of 5-chloro	-2-methyl-2H	l-isothiazol-3	-one and 2-methyl-2H-isc	othiazol-3-one (3:1)	
	oral	ATE mg/kg	100			
	dermal	ATE	50 mg/kg			
	inhalation vapour	ATE	0,5 mg/l			
	inhalation aerosol	ATE	0,05 mg/l			

Further information

There are no data available on the mixture itself.

The classification was carried out according to the calculation method of the Preparations Directive

```
(1999/45/EC).
```

Reference to other sections: 2, 3

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d] Species	Source	Method
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether				
	Acute fish toxicity	LC50 1490 mg/l	96 h Lepomis macrochirus		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

according to Regulation (EC) No 1907/2006

OLI-AQUA MODU B 18.35

Revision date: 01.10.2021

Product code: A00809

Page 7 of 9

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether	0,81 (25°C)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.7. Other adverse effects

No data available

Further information

There are no data available on the mixture itself. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose according to legislation.

List of Wastes Code - residues/unused products

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

List of Wastes Code - used product

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

List of Wastes Code - contaminated packaging

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Contaminated packaging

Completely emptied packages can be recycled. Dispose according to legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

Other applicable information (land transport)

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

Other applicable information (marine transport) No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)

according to Regulation (EC) No 1907/2006

Revision date: 01.10.2021

Product code: A00809

Page 8 of 9

Other applicable information (air transport) No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

refer to chapter 7. No further action is necessary.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	EU regulatory information Restrictions on use (REACH, annex XVII): Entry 28	
2	2004/42/EC (VOC):	96 g/l
N	lational regulatory information	
۷	Vater hazard class (D):	1 - slightly hazardous to water
A	Additional information	
	Observe in addition any national regulat	tions!

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one,
	2-methylisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and
	2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

according to Regulation (EC) No 1907/2006

OLI-AQUA MODU B 18.35

Revision date: 01.10.2021

Product code: A00809

Page 9 of 9

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)