

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## OLI-CRYL 25.80 2K Hochglanzlack

Revision date: 03.04.2019

Product code: A01074

Page 1 of 9

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

OLI-CRYL 25.80 2K Hochglanzlack

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Colour

#### 1.3. Details of the supplier of the safety data sheet

Company name:	Oli Lacke GmbH	
Street:	Bahnhofstrase 22	
Place:	D-09244 Lichtenau	
Telephone:	+49(0)37208/84200	Telefax: +49(0)37208/84268
e-mail:	entwicklung@oli-lacke.de	
Internet:	www.oli-lacke.de	

#### 1.4. Emergency telephone

**number:** Gemeins. Gifinformationszentrum Erfurt

+49(0)361/730730

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

n-butyl acetate

Lösungsmittelnaphtha leicht, Benzolgehalt < 0,1 Gew. %

2-ethoxy-1-methylethyl acetate, 2PG1EEA

**Signal word:** Warning

##### Pictograms:



##### Hazard statements

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P273	Avoid release to the environment.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-CRYL 25.80 2K Hochglanzlack

Revision date: 03.04.2019

Product code: A01074

Page 2 of 9

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P405 Store locked up.

#### Special labelling of certain mixtures

EUH208 Contains dipentene, limonene. May produce an allergic reaction.

#### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
123-86-4	n-butyl acetate			20 - < 25 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
64742-95-6	Lösungsmittelnaphtha leicht, Benzolgehalt < 0,1 Gew. %			10 - < 15 %
	265-199-0		01-2119455851-35	
	STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H336 H304 H411			
54839-24-6	2-ethoxy-1-methylethyl acetate, 2PG1EEA			5 - < 10 %
	259-370-9	603-177-00-8		
	Flam. Liq. 3, STOT SE 3; H226 H336			
1330-20-7	xylene			5 - < 10 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
108-65-6	2-methoxy-1-methylethyl acetate			5 - < 10 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3; H226			
138-86-3	dipentene, limonene			< 1 %
	205-341-0	601-029-00-7		
	Flam. Liq. 3, Skin Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H226 H315 H317 H400 H410			

Full text of H and EUH statements: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

##### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**OLI-CRYL 25.80 2K Hochglanzlack**

Revision date: 03.04.2019

Product code: A01074

Page 3 of 9

**After contact with skin**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

**After contact with eyes**

Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Impaired consciousness

**4.3. Indication of any immediate medical attention and special treatment needed**

Immediately call a doctor.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. Water mist

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Burning produces heavy smoke. Hazardous decomposition products: carbon black Danger of serious damage to health by prolonged exposure. Use appropriate respiratory protection.

**5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition - No smoking. Provide adequate ventilation. In case of fire and/or explosion do not breathe fumes. Safe handling: see section 7 Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Observe in addition any national regulations! In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

**6.4. Reference to other sections**

See section 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Even after use and until complete evaporation of the flammable components, there is still a danger of an explosive steam-air mixture forming. Only use the material in places where open light, fire and other flammable sources

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-CRYL 25.80 2K Hochglanzlack

Revision date: 03.04.2019

Product code: A01074

Page 4 of 9

can be kept away. Take precautionary measures against static discharges. Use explosion-proof electrical equipment. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles When using do not eat, drink or smoke. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

#### Advice on protection against fire and explosion

Concentrated vapours are heavier than air. Vapours may form explosive mixtures with air.

#### Further information on handling

Observe in addition any national regulations!

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Betriebssicherheitsverordnung (BetrSichV)

##### Advice on storage compatibility

Von stark sauren oder alkalischen Materialien oder Oxidationsmitteln fernhalten.

##### Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place. Keep away from heat. Notice the directions for use on the label. Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

#### 7.3. Specific end use(s)

Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

### 8.2. Exposure controls

#### Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-CRYL 25.80 2K Hochglanzlack

Revision date: 03.04.2019

Product code: A01074

Page 5 of 9

#### Protective and hygiene measures

Wash hands before breaks and after work. Do not eat, drink, smoke or sneeze at the workplace.

#### Eye/face protection

Tightly sealed safety glasses.

#### Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Use protective skin cream before handling the product.

#### Skin protection

Protective clothing: Natural fibres (e.g. cotton) heat-resistant synthetic fibres

#### Respiratory protection

During spraying wear suitable respiratory equipment. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid  
Colour:

#### Test method

#### Changes in the physical state

Flash point:	> 23 °C	DIN EN ISO 1523
Lower explosion limits:	0,7 vol. %	
Upper explosion limits:	9,8 vol. %	
Ignition temperature:	325 °C	
Vapour pressure: (at 20 °C)	11,6 hPa	
Density (at 20 °C):	0,999 g/cm <sup>3</sup>	ISO 2811
Flow time: (at 20 °C)	25 s	4 DIN 53211
Solvent separation test:	< 3 %	
Solvent content:	56 %	
<b>9.2. Other information</b>		
Solid content:	44 %	

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

refer to chapter 7. No further action is necessary.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Exothermic reactions with: Alkalis (alkalis), concentrated. Acid, concentrated. Oxidizing agents, strong.

#### 10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapours.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-CRYL 25.80 2K Hochglanzlack

Revision date: 03.04.2019

Product code: A01074

Page 6 of 9

#### 10.5. Incompatible materials

Rubber articles

#### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Nitrogen oxides (NOx).

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalative vapour	ATE 11 mg/l			
	inhalative aerosol	ATE 1,5 mg/l			
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 8532 mg/kg	Rat	RTECS	
	dermal	LD50 7500 mg/kg	Rabbit		

##### Carcinogenic/mutagenic/toxic effects for reproduction

The components in this formulation do not meet the criteria for classification as CMR category 1 or 2.

##### Additional information on tests

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

### SECTION 12: Ecological information

#### 12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 161 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 408 mg/l	48 h	Daphnia magna		

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

##### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-65-6	2-methoxy-1-methylethyl acetate	0,43

#### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-CRYL 25.80 2K Hochglanzlack

Revision date: 03.04.2019

Product code: A01074

Page 7 of 9

#### **12.6. Other adverse effects**

There are no data available on the preparation/mixture itself.

#### **Further information**

There are no data available on the preparation/mixture itself. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

### **SECTION 13: Disposal considerations**

#### **13.1. Waste treatment methods**

##### **Advice on disposal**

Do not allow to enter into surface water or drains.  
Dispose according to legislation.

##### **Waste disposal number of waste from residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### **Waste disposal number of used product**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### **Waste disposal number of contaminated packaging**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

### **SECTION 14: Transport information**

#### **Land transport (ADR/RID)**

<b><u>14.1. UN number:</u></b>	UN 1263
<b><u>14.2. UN proper shipping name:</u></b>	Paint
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	3
Classification code:	F1
Special Provisions:	163 367 650
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

#### **Inland waterways transport (ADN)**

<b><u>14.1. UN number:</u></b>	UN 1263
<b><u>14.2. UN proper shipping name:</u></b>	Paint
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### OLI-CRYL 25.80 2K Hochglanzlack

Revision date: 03.04.2019

Product code: A01074

Page 8 of 9

Classification code:	F1
Special Provisions:	163 367 650
Limited quantity:	5 L
Excepted quantity:	E1

#### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	Paint
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
Special Provisions:	163, 223, 367, 955
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	Paint
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
Special Provisions:	A3 A72 A192
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.6. Special precautions for user

refer to chapter 7. No further action is necessary.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Lösungsmittelnaphtha leicht, Benzolgehalt < 0,1 Gew. %

2004/42/EC (VOC): 559 g/l

##### National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

##### Additional information

Observe in addition any national regulations!

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**OLI-CRYL 25.80 2K Hochglanzlack**

Revision date: 03.04.2019

Product code: A01074

Page 9 of 9

**SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains dipentene, limonene. May produce an allergic reaction.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*