

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Revision date: 16.04.2020

Product code: A00706

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

OLI-AQUA TOP 2K Parkettsiegel 51.20

Further trade names

OLI-AQUA TOP
2K Parkettsiegel 51.20
diverse Glanzgrade

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Colour

1.3. Details of the supplier of the safety data sheet

Company name:	Oli Lacke GmbH	
Street:	Bahnhofstrasse 22	
Place:	D-09244 Lichtenau	
Telephone:	+49(0)37208/84200	Telefax: +49(0)37208/84268
e-mail:	entwicklung@oli-lacke.de	
Internet:	www.oli-lacke.de	

1.4. Emergency telephone

Gemeins. Gifinformationszentrum Erfurt

number: +49(0)361/730730

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements

Regulation (EC) No. 1272/2008

Precautionary statements

P102 Keep out of reach of children.

Special labelling of certain mixtures

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether			1 - < 5 %
	203-961-6	603-096-00-8	01-2119475104-44	
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Revision date: 16.04.2020

Product code: A00706

Page 2 of 8

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.
After contact with skin, wash immediately with plenty of water and soap.
Do not wash with: Solvents/Thinner

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.
Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Impaired consciousness

4.3. Indication of any immediate medical attention and special treatment needed

Call a physician immediately.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.
Hazardous decomposition products: carbon black. Danger of serious damage to health by prolonged exposure.
Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Contains: Solvent - Keep away from sources of ignition - No smoking. Ventilate affected area.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Safe handling: see section 7
Personal protection equipment: see section 8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Revision date: 16.04.2020

Product code: A00706

Page 3 of 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal. Disposal: see section 13

Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

See section 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Contains: Solvent - In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof electrical equipment.

Never use pressure to empty container. Keep/Store only in original container. Do not allow to enter into surface water or drains. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV)

Hints on joint storage

Do not store together with: Oxidising agent, Strong acid, Strong alkali

Further information on storage conditions

Notice the directions for use on the label.

storage temperature of °C 5 up to °C 30

Contains: Solvent - Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Revision date: 16.04.2020

Product code: A00706

Page 4 of 8

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
34590-94-8	(2-methoxymethylethoxy) propanol	50	308		TWA (8 h)	WEL
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
108-01-0	2-Dimethylaminoethanol	2	7.4		TWA (8 h)	WEL
		6	22		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Eye/face protection

Wear eye/face protection.

Hand protection

Wear suitable gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. See information supplied by the manufacturer.

Suitable material: NBR (Nitrile rubber).

Use protective skin cream before handling the product.

Skin protection

Wear anti-static footwear and clothing (Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.

Use suitable breathing apparatus.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour:

Test method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Revision date: 16.04.2020

Product code: A00706

Page 5 of 8

pH-Value (at 20 °C):	7 - 9
Changes in the physical state	
Initial boiling point and boiling range:	100 °C
Flash point:	> 60 °C DIN EN ISO 1523
Lower explosion limits:	0,8 vol. %
Upper explosion limits:	5,9 vol. %
Ignition temperature:	204 °C
Vapour pressure: (at 20 °C)	31,6 hPa
Density (at 20 °C):	1,05 g/cm ³ ISO 2811
Flow time: (at 20 °C)	verarbeitungsfertig
Solvent separation test:	< 3 %
Solvent content:	4,5 %
9.2. Other information	
Solid content:	32 %

SECTION 10: Stability and reactivity

10.1. Reactivity

refer to chapter 7. No further action is necessary.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent, Strong acid, Strong alkali

10.4. Conditions to avoid

In case of warming: Formation of: Hazardous decomposition products

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO₂), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether				
	oral	LD50 mg/kg	5660	Rat	
	dermal	LD50 mg/kg	4120	Rabbit	

Further information

There are no data available on the mixture itself.

The classification was carried out according to the calculation method of the Preparations Directive

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Revision date: 16.04.2020

Product code: A00706

Page 6 of 8

(1999/45/EC).

Reference to other sections: 2, 3

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether					
	Acute algae toxicity	ErC50 mg/l	> 100		Scenedesmus sp.	
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	0,56 (25°C)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

There are no data available on the mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.

Dispose according to legislation.

List of Wastes Code - residues/unused products

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

List of Wastes Code - used product

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

List of Wastes Code - contaminated packaging

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Revision date: 16.04.2020

Product code: A00706

Page 7 of 8

Contaminated packaging

Completely emptied packages can be recycled.
Dispose according to legislation.

SECTION 14: Transport information**Land transport (ADR/RID)****Other applicable information (land transport)**

No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)**Other applicable information (inland waterways transport)**

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)**Other applicable information (marine transport)**

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)**Other applicable information (air transport)**

No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

refer to chapter 7. No further action is necessary.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 55: 2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether

2004/42/EC (VOC): 47 g/l
gehärtet: 75 g/l

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H319 Causes serious eye irritation.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OLI-AQUA TOP 2K Parkettsiegel 51.20

Revision date: 16.04.2020

Product code: A00706

Page 8 of 8

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)